


FLEXIBLE INSTALLATION

UniMac softmount washer-extractors not only save on utility costs, but on installation time and costs as well. The freestanding design installs quickly with same-day operation. These machines are the perfect choice for second-floor laundries or other installations, where a concrete floor isn't an option. Heavy-duty coil springs eliminate the need for special foundations, and strategically placed shock absorbers result in a tuned suspension system that absorbs out-of-balance load vibrations.

TAKE CONTROL OF YOUR LAUNDRY

PROFORM CONTROL

The cutting-edge PROform Control features 99 programming options, eight liquid chemical soap connections, multi-language capability and a variety of extra functions, from soak to advanced start. Easy and intuitive, the graphical display provides numeric keypads and is organized for simple control and navigation. Update wash programs manually on the machine, use a USB memory stick or update on your PC via LMS. Additionally, an end-of-cycle signal allows you to maximize throughput.



INDUSTRY-LEADING DURABILITY

Our softmount washer-extractors are manufactured with unyielding construction and industrial strength. They're designed with high-quality stainless steel front, top and side panels for increased strength and durability. The formed steel frame is engineered with robust technology for added strength. And a modular bearing housing design ensures the equipment is long lasting and easy to service. This product also offers an inverter drive system that delivers low energy use, higher torque, high extraction speed, lower noise of 71-72 dBA (one of the best on the market) and less imbalance.

UY SERIES AT A GLANCE

- High-quality, stainless steel front and side panels
- Stainless-steel inner drum and tub
- Two large drain valves for faster cycle times
- Eight liquid chemical connections
- Inverter drive system for lower energy use
- Stainless steel door frame with extra large door opening for easy loading and unloading
- Chemical dispenser with five removable compartments, providing easy access
- Ozone-compatible design
- Oversized steel shaft
- Durable micro-v belt for long life
- Strong, oversized door lock and wide-set door hinges for stability



UY SERIES SOFTMOUNT WASHER-EXTRACTORS 90-275 LB

SPECIFICATIONS	UY90	UY125	UY180	UY230	UY275
Control	PROform	PROform	PROform	PROform	PROform
Capacity - lb (kg)	90 (40)	125 (55)	180 (80)	230 (100)	275 (120)
Tilt Option			Option	Option	Option
Dimensions w/o Tilt	-	-	-	-	-
Width - in (mm)	47 (1195)	47 (1195)	58 7/8 (1495)	70 1/2 (1790)	73 (1855)
Depth - in (mm)	56 1/2 (1430)	63 3/8 (1610)	76 3/8 (1940)	78 15/16 (2005)	82 1/8 (2085)
Height - in (mm)	75 (1905)	75 (1905)	78 1/8 (1985)	81 1/8 (2060)	82 1/8 (2085)
Dimensions w/ Tilt	-	-	-	-	-
Width - in (mm)			61 5/8 (1565)	72 7/8 (1855)	74 9/16 (1895)
Depth - in (mm)			93 11/16 (2380)	99 3/4 (2534)	100 1/2 (2553)
Height - in (mm)			97 1/2 (2476)	101 3/8 (2575)	103 1/2 (2628)
Cylinder Diameter - in (mm)	36 (914)	36 (914)	43 11/16 (1110)	47 1/4 (1200)	51 3/16 (1300)
Cylinder Depth - in (mm)	24 (610)	31 1/8 (790)	33 (838)	33 7/8 (860)	34 1/4 (870)
Cylinder Volume - cu. ft. (liters)	14.1 (400)	18.3 (518)	28.5 (807)	34.3 (972)	40.8 (1154)
Door Opening Size - in (mm)	21 5/16 (540)	21 5/16 (540)	20 7/8 (530)	20 7/8 (530)	25 5/8 (650)
Door Bottom to Floor - in (mm)	28 3/4 (730)	28 3/4 (730)	40 1/8 (1020)	43 1/8 (1095)	42 1/2 (1080)
Wash Speed - RPM	38	38	36	33	32
Extract Speed - RPM	830	830	750	720	695
Extract G-Force	350	350	350	350	350
Water Inlet Conn. - in (mm)	3 x 1 (25)	3 x 1 (25)	3 x 1 1/2 (38)	3 x 1 1/2 (38)	3 x 1 1/2 (38)
Steam Inlet Conn. - in (mm)	3/4 (19)	3/4 (19)	1 (25)	1 (25)	1 (25)
Drain Conn. Size - in (mm)	2 x 3 (76)	2 x 3 (76)	2 x 4 (103)	2 x 4 (103)	2 x 4 (103)
Motor Size - HP (kW)	10.06 (7.50)	10.06 (7.50)	14.75 (11.00)	20.12 (15.00)	24.81 (18.50)
Voltage/Hz/Phase Circuit/	220-240V/50-60Hz/3ph 400-480V/50/60Hz/3ph	220-240V/50-60Hz/3ph 400-480V/50/60Hz/3ph	208-240V/50-60Hz/3ph 400-480V/50/60Hz/3ph	208-240V/50-60Hz/3ph 400-480V/50/60Hz/3ph	208-240V/50-60Hz/3ph 400-480V/50/60Hz/3ph
Shipping Dimensions w/o Tilt	-	-	-	-	-
Height - in (mm)	82 15/16 (2105)	82 15/16 (2105)	86 5/8 (2200)	92 5/16 (2345)	92 1/8 (2340)
Width - in (mm)	56 5/16 (1430)	56 5/16 (1430)	66 1/2 (1690)	73 7/16 (1865)	78 3/4 (2000)
Depth - in (mm)	61 13/16 (1570)	68 7/8 (1750)	76 3/4 (1950)	83 11/16 (2125)	85 7/16 (2170)
Shipping Dimensions w/ Tilt	-	-	-	-	-
Height - in (mm)			96 1/16 (2440)	98 (2490)	98 (2490)
Width - in (mm)			66 1/2 (1690)	80 5/16 (2040)	80 5/16 (2040)
Depth - in (mm)			81 11/16 (2075)	93 1/2 (2375)	93 1/2 (2375)
Net Weight - lb (kg) w/o Tilt	3439 (1560)	3594 (1630)	5820 (2640)	6989 (3170)	7672 (3480)
Net Weight - lb (kg) w/ Tilt			6592 (2990)	7760 (3520)	8466 (3840)
Shipping Weight - lb (kg) w/o Tilt	3748 (1700)	3902 (1770)	6239 (2830)	7518 (3410)	8179 (3710)
Shipping Weight - lb (kg) w/ Tilt			7077 (3210)	8289 (3760)	8951 (4060)
Agency Approvals	CSA	CSA	CSA	CSA	CSA

**TO LEARN MORE OR TO FIND A DISTRIBUTOR IN YOUR AREA, VISIT UNIMAC.COM
ALLIANCE LAUNDRY SYSTEMS - SHEPARD ST, RIPON, WI 54971 - 1.800.587.5458**

For the most accurate information, the installation guide should be used for all design and construction purposes. Due to continuous product improvements, design and specifications subject to change without notice. The quality management systems at Alliance Laundry Systems are registered to ISO 9001.