



Equipment for the Foodservice Industry



# Merchandisers

by EFI



VERSA-CHILL SERIES

# Top Mount Reach-in Glass Door Refrigeration & Freezers

C1-29GDSVC  
F1-29GDSVC



Merchandisers

**C1-29GDSVC  
F1-29GDSVC**

**Features**

- Top mount compressor units
- Environmentally friendly R290 refrigerant
- LED lighting interior display system
- Dixell digital temperature control system
- Heavy duty Embraco compressor
- Self-closing and stay open door
- Efficient refrigeration system
- For optimum food preservation refrigeration units hold 33°F to 45°F (0.5°C to 8°C), freezer units hold -4°F to 1°F (-20°C to -18°C)
- Recessed door handle
- Standard safety door lock
- Magnetic door gaskets
- Pre-installed casters
- Pre-installed shelves

Model	Doors	Shelves	Dimension (mm)			HP	Voltage	Amps	Capacity Cu Ft. (L)	Net Weight lb (kg)	NEMA Config.
			L"	D"	H"						
<b>REFRIGERATION</b>											
C1-29GDSVC	1	4	30.3 (770)	34.6 (880)	85.8 (2180)	1/6	115/60	2.1	21.4 (606)	264 (120)	5-15P
<b>FREEZER</b>											
F1-29GDSVC	1	4	30.3 (770)	34.6 (880)	85.8 (2180)	1/2	115/60	6.3	21.4 (606)	264 (120)	5-15P

>> **Refrigeration Warranty:** 2 year parts and labour; 5 years on compressor; full details on page 226

Specifications subject to change without notice.



VERSA-CHILL SERIES

# Top Mount Reach-in Glass Door Refrigeration & Freezers

C2-52GDSVC  
F2-52GDSVC



Merchandisers

**C2-52GDSVC  
F2-52GDSVC**

**Features**

- Top mount compressor units
- Environmentally friendly R290 refrigerant
- LED lighting interior display system
- Dixell digital temperature control system
- Heavy duty Embraco compressor
- Self-closing and stay open door
- Efficient refrigeration system
- For optimum food preservation refrigeration units hold 33°F to 45°F (0.5°C to 8°C), freezer units hold -4°F to 1°F (-20°C to -18°C)
- Recessed door handle
- Standard safety door lock
- Magnetic door gaskets
- Pre-installed casters
- Pre-installed shelves

Model	Doors	Shelves	Dimension (mm)			HP	Voltage	Amps	Capacity Cu Ft. (L)	Net Weight lb (kg)	NEMA Config.
			L"	D"	H"						
<b>REFRIGERATION</b>											
C2-52GDSVC	2	8	53.4 (1355)	34.6 (880)	85.8 (2180)	1/3	115/60	3.2	43.2 (1222)	440 (200)	5-15P
<b>FREEZER</b>											
F2-52GDSVC	2	8	53.4 (1355)	34.6 (880)	85.8 (2180)	3/4	115/60	8.6	43.2 (1222)	440 (200)	5-15P

>> **Refrigeration Warranty:** 2 year parts and labour; 5 years on compressor; full details on page 226



Specifications subject to change without notice.

VERSA-CHILL SERIES

# Top Mount Reach-in Glass Door Freezers

F3-78GDSVC



Merchandisers

**F3-78GDSVC**

**Features**

- Top mount compressor units
- Environmentally friendly R290 refrigerant
- LED lighting interior display system
- Dixell digital temperature control system
- Heavy duty Embraco compressor
- Self-closing and stay open door
- Efficient refrigeration system
- For optimum food preservation freezer units hold -4°F to 1°F (-20°C to -18°C)
- Recessed door handle
- Standard safety door lock
- Magnetic door gaskets
- Pre-installed casters
- Pre-installed shelves

Model	Doors	Shelves	Dimension (mm)			HP	Voltage	Amps	Capacity Cu Ft. (L)	Net Weight lb (kg)	NEMA Config.
			L"	D"	H"						
<b>FREEZER</b>											
F3-78GDSVC	3	12	77.8 (1976)	31.7 (805)	81.3 (2065)	1	115/208- 230V	5.5	67 (1900)	506 (230)	L14-20P

>> **Refrigeration Warranty:** 2 year parts and labour; 5 years on compressor; full details on page 226

Specifications subject to change without notice.



VERSA-CHILL SERIES

# Bottom Mount Reach-in Glass Door Refrigeration & Freezers

C1-27GDSVC  
F1-27GDSVC



**C1-27GDSVC  
F1-27GDSVC**

**Features**

- Bottom mount compressor units
- Environmentally friendly R290 refrigerant
- LED lighting interior display system
- Dixell digital temperature control system
- Heavy duty Embraco compressor
- Self-closing and stay open door
- Efficient refrigeration system
- For optimum food preservation refrigeration units hold 33°F to 45°F (0.5°C to 8°C), freezer units hold -4°F to 1°F (-20°C to -18°C)
- Recessed door handle
- Standard safety door lock
- Magnetic door gaskets
- Pre-installed casters
- Pre-installed shelves

Model	Doors	Shelves	Dimension (mm)			HP	Voltage	Amps	Capacity Cu Ft. (L)	Net Weight lb (kg)	NEMA Config.
			L"	D"	H"						
<b>REFRIGERATION</b>											
C1-27GDSVC	1	4	27 (685)	31.5 (800)	84.1 (2135)	1/6	115/60	2.1	19.1 (541)	293 (133)	5-15P
<b>FREEZER</b>											
F1-27GDSVC	1	4	27 (685)	31.5 (800)	84.1 (2135)	1/2	115/60	6.3	19.1 (541)	308 (140)	5-15P

>> **Refrigeration Warranty:** 2 year parts and labour; 5 years on compressor; full details on page 226



Specifications subject to change without notice.

VERSA-CHILL SERIES

# Bottom Mount Reach-in Glass Door Refrigeration & Freezers

C2-39GDSVC, C2-54GDSVC  
F2-54GDSVC



**C2-39GDSVC, C2-54GDSVC  
F2-54GDSVC** **Features**

- Bottom mount compressor units
- Environmentally friendly R290 refrigerant
- LED lighting interior display system
- Dixell digital temperature control system
- Heavy duty Embraco compressor
- Self-closing and stay open door
- Efficient refrigeration system
- For optimum food preservation refrigeration units hold 33°F to 45°F (0.5°C to 8°C), freezer units hold -4°F to 1°F (-20°C to -18°C)
- Recessed door handle
- Standard safety door lock
- Magnetic door gaskets
- Pre-installed casters
- Pre-installed shelves

Model	Doors	Shelves	Dimension (mm)			HP	Voltage	Amps	Capacity Cu Ft. (L)	Net Weight lb (kg)	NEMA Config.
			L"	D"	H"						
<b>REFRIGERATION</b>											
C2-39GDSVC	2	8	39.5 (1003)	31.5 (800)	84.1 (2135)	1/4+	115/60	6.5	35.3 (1000)	418 (190)	5-15P
C2-54GDSVC	2	8	54.4 (1382)	31.5 (800)	84.1 (2135)	1/3	115/60	3.2	448 (1268)	484 (220)	5-15P
<b>FREEZER</b>											
F2-54GDSVC	2	8	54.4 (1382)	31.5 (800)	84.1 (2135)	3/4	115/60	8.6	448 (1268)	484 (220)	5-15P

>> **Refrigeration Warranty:** 2 year parts and labour; 5 years on compressor; full details on page 226

Specifications subject to change without notice.



VERSA-CHILL SERIES

# Bottom Mount Reach-in Glass Door Freezers

F3-82GDSVC



**F3-82GDSVC**

**Features**

- Bottom mount compressor units
- Environmentally friendly R290 refrigerant
- LED lighting interior display system
- Dixell digital temperature control system
- Heavy duty Embraco compressor
- Self-closing and stay open door
- Efficient refrigeration system
- For optimum food preservation freezer units hold -4°F to 1°F (-20°C to -18°C)
- Recessed door handle
- Standard safety door lock
- Magnetic door gaskets
- Pre-installed casters
- Pre-installed shelves

Model	Doors	Shelves	Dimension (mm)			HP	Voltage	Amps	Capacity Cu Ft. (L)	Net Weight lb (kg)	NEMA Config.
			L"	D"	H"						
<b>FREEZER</b>											
F3-82GDSVC	3	12	819 (2079)	31.5 (800)	84.1 (2135)	1	115/208-230V	5.5	74.5 (2110)	489 (222)	L14-20P

>> **Refrigeration Warranty:** 2 year parts and labour; 5 years on compressor; full details on page 226



Specifications subject to change without notice.

VERSA-CHILL SERIES

# Glass Door Merchandiser Refrigeration & Freezers

C1-23GDVC, C1-24GDVC  
C1-27GDVC  
F1-27GDVC



Merchandisers

**C1-23GDVC, C1-24GDVC  
C1-27GDVC  
F1-27GDVC**

**Features**

- Bottom mount compressor units
- Environmentally friendly R290 refrigerant
- LED lighting interior display system
- Dixell digital temperature control system
- Heavy duty Embraco compressor
- Self-closing and stay open door
- Efficient refrigeration system
- For optimum food preservation refrigeration units hold 33°F to 45°F (0.5°C to 8°C), freezer units hold -4°F to 1°F (-20°C to -18°C)
- Recessed door handle
- Standard safety door lock
- Magnetic door gaskets
- Pre-installed casters
- Pre-installed shelves

Model	Doors	Shelves	Dimension (mm)			HP	Voltage	Amps	Capacity Cu Ft. (L)	Net Weight lb (kg)	NEMA Config.
			L"	D"	H"						
<b>REFRIGERATION</b>											
C1-23GDVC	1	3	24.2 (615)	24 (610)	61.4 (1560)	1/6	115/60	2.1	8.3 (235)	189 (86)	5-15P
C1-24GDVC	1	4	24.2 (615)	24 (610)	76.2 (1935)	1/6	115/60	2.1	11.1 (314)	227 (103)	5-15P
C1-27GDVC	1	4	27 (685)	31.5 (800)	81.2 (2062)	1/6	115/60	2.1	19.4 (549)	293 (133)	5-15P
<b>FREEZER</b>											
F1-27GDVC	1	4	27 (685)	31.5 (800)	81.2 (2062)	1/2	115/60	6.3	19.2 (542)	308 (140)	5-15P

>> **Refrigeration Warranty:** 2 year parts and labour; 5 years on compressor; full details on page 226

Specifications subject to change without notice.





VERSA-CHILL SERIES

# Glass Door Merchandiser Refrigeration & Freezers

C2-54GDVC  
F2-54GDVC



Merchandisers

**C2-54GDVC**  
**F2-54GDVC**

**Features**

- Bottom mount compressor units
- Environmentally friendly R290 refrigerant
- LED lighting interior display system
- Dixell digital temperature control system
- Heavy duty Embraco compressor
- Self-closing and stay open door
- Efficient refrigeration system
- For optimum food preservation refrigeration units hold 33°F to 45°F (0.5°C to 8°C), freezer units hold -4°F to 1°F (-20°C to -18°C)
- Recessed door handle
- Standard safety door lock
- Magnetic door gaskets
- Pre-installed casters
- Pre-installed shelves

Model	Doors	Shelves	Dimension (mm)			HP	Voltage	Amps	Capacity Cu Ft. (L)	Net Weight lb (kg)	NEMA Config.
			L"	D"	H"						
<b>REFRIGERATION</b>											
C2-54GDVC	2	8	54.4 (1382)	31.5 (800)	81.2 (2062)	1/3	115/60	3.2	43.5 (1320)	484 (220)	5-15P
<b>FREEZER</b>											
F2-54GDVC	2	8	54.4 (1382)	31.5 (800)	81.2 (2062)	3/4	115/60	8.6	43.5 (1320)	497 (226)	5-15P

>> **Refrigeration Warranty:** 2 year parts and labour; 5 years on compressor; full details on page 226



Specifications subject to change without notice.

VERSA-CHILL SERIES

# Glass Door Merchandiser Refrigeration & Freezers

C3-82GDVC  
F3-82GDVC



Merchandisers

**C3-82GDVC**  
**F3-82GDVC**

**Features**

- Bottom mount compressor units
- Environmentally friendly R290 refrigerant
- LED lighting interior display system
- Dixell digital temperature control system
- Heavy duty Embraco compressor
- Self-closing and stay open door
- Efficient refrigeration system
- For optimum food preservation refrigeration units hold 33°F to 45°F (0.5°C to 8°C), freezer units hold -4°F to 1°F (-20°C to -18°C)
- Recessed door handle
- Standard safety door lock
- Magnetic door gaskets
- Pre-installed casters
- Pre-installed shelves
- Freezer unit NEMA configuration L14-20



Model	Doors	Shelves	Dimension (mm)			HP	Voltage	Amps	Capacity Cu Ft. (L)	Net Weight lb (kg)	NEMA Config.
			L"	D"	H"						
<b>REFRIGERATION</b>											
C3-82GDVC	3	12	81.9 (2079)	31.5 (800)	81.2 (2062)	1/3	115/60	4.2	69.5 (1969)	651 (296)	5-15P
<b>FREEZER</b>											
F3-82GDVC	3	12	81.9 (2079)	31.5 (800)	81.2 (2062)	1	115/208-230V	5.5	72.5 (2050)	651 (296)	L14-20P

>> **Refrigeration Warranty:** 2 year parts and labour; 5 years on compressor; full details on page 226

Specifications subject to change without notice.



CLASSIC CHILL SERIES

# Glass Door Merchandiser Refrigeration

C2-54GDCC



Merchandisers

**C2-54GDCC**

**Features**

- Evaporator fan motor that stops when door is open to conserve energy
- Removable gasket that is easy to clean and replace
- Adjustable/removable plastic coated wire shelves - Shelves can be set-up to hold standard full size hotel pans
- Bottom-mounted cooling unit is easy to remove and clean
- Outstanding temperature preservation reduces energy consumption via foamed-in polyurethane cell insulation
- Auto evaporation of defrosting water
- Round corner design for inner bottom shelf to facilitate easy cleaning
- Cold air circulation via fan for temperature balance
- For optimum food preservation refrigeration units hold 33°F to 45°F (0.5°C to 8°C), freezer units hold -4°F to 1°F (-20°C to -18°C)

Model	Doors	Shelves	Dimension (mm)			HP	Voltage	Amps	Capacity Cu Ft. (L)	Net Weight lb (kg)	NEMA Config.
			L"	D"	H"						
<b>REFRIGERATION</b>											
C2-54GDCC	2	8	54 (1371)	32.2 (818)	82.5 (2095)	1/4+	115/60	4	47 (1330)	458 (207.7)	5-15P

>> **Refrigeration Warranty:** 2 year parts and labour; 5 years on compressor; full details on page 226



*Specifications subject to change without notice.*

# Glass Door Merchandiser Refrigeration

C1-21GD



Merchandisers

**C1-21GD**

**Features**

- Exterior - coated steel
- Interior - attractive, aluminum liner with stainless steel floor
- Rounded corner design inside of the cabinet makes it easy to clean the inside storage room
- Double pane glass door, self-closing
- Positive seal, torsion type closure system
- R290 Refrigeration system holds 33°F to 41°F (0.5°C to 5°C), ideal for beverage and soft drinks
- Adjustable temperature set point and defrost frequency
- Error codes to diagnose service issues
- Adjustable, heavy duty PVC coated shelves
- LED light
- "No stoop" lower shelf
- Easily accessible condenser coil for cleaning, and easy service access
- Simple installation with no plumbing required

Model	Doors	Shelves	Dimension (mm)			HP	Voltage	Amps	Capacity Cu Ft. (L)	Net Weight lb (kg)	NEMA Config.
			L"	D"	H"						
<b>REFRIGERATION</b>											
C1-21GD	1	4	21.6 (550)	21.6 (550)	63 (1600)	1/4	115/60	2.88	9 (258)	203 (92)	5-15P

>> **Refrigeration Warranty:** 2 year parts and labour; 5 years on compressor; full details on page 226

Specifications subject to change without notice.



# Glass Door Merchandiser Refrigeration

C1-23GD, C1-27GD  
F1-27GD, F1-31GD



**C1-23GD, C1-27GD  
F1-27GD, F1-31GD** **Features**

- Evaporator fan motor that stops when door is open to conserve energy
- Removable gasket that is easy to clean and replace
- Adjustable/removable plastic coated wire shelves - Shelves can be set-up to hold standard full size hotel pans
- Bottom-mounted cooling unit is easy to remove and clean
- Outstanding temperature preservation reduces energy consumption via foamed-in polyurethane cell insulation
- Auto evaporation of defrosting water
- Round corner design for inner bottom shelf to facilitate easy cleaning
- Cold air circulation via fan for temperature balance
- Refrigeration unit holds 33°F to 41°F (0.5°C to 5°C), freezer units hold -10°F to 0°F (-23°C to -18°C)

Model	Doors	Shelves	Dimension (mm)			HP	Voltage	Amps	Capacity Cu Ft. (L)	Net Weight lb (kg)	NEMA Config.
			L"	D"	H"						
<b>REFRIGERATION</b>											
C1-23GD	1	4	25.6 (650.2)	22.9 (581.7)	79.4 (2016.8)	1/5	115/60	2.88	14 (398)	209 (94.8)	5-15P
C1-27GD	1	4	28.4 (821.4)	31.9 (810.3)	79.4 (2016.8)	1/5	115/60	3	23 (648)	353 (160)	5-15P
<b>FREEZER</b>											
F1-27GD	1	4	27.4 (696)	27.5 (698.6)	80.4 (2042.2)	3/4	115/60	8.8	13 (368.1)	254 (115)	5-15P
F1-31GD	1	4	31.1 (789.9)	31.3 (795)	80.8 (2052.3)	3/4	115/60	9.4	23 (648)	397 (180)	5-15P

>> **Refrigeration Warranty:** 2 year parts and labour; 5 years on compressor; full details on page 226



Specifications subject to change without notice.

# Glass Door Merchandiser Refrigeration

C1-25GD  
C1-28GD



Merchandisers

**C1-25GD  
C1-28GD**

**Features**

- Exterior - coated steel
- Interior - attractive, aluminum liner with stainless steel floor.
- Rounded corner design inside of the cabinet makes it easy to clean the inside storage room
- Double pane glass door.
- Self-closing. Positive seal, torsion type closure system.
- R290 Refrigeration system holds 33°F to 41°F (0.5°C to 5°C), ideal for beverage and soft drinks.
- Adjustable temperature set point and defrost frequency. Error codes to diagnose service issues.
- Adjustable, heavy duty PVC coated shelves.
- LED light
- "No stoop" lower shelf.
- Easily accessible condenser coil for cleaning, and easy service access
- Simple installation with no plumbing required.

Model	Doors	Shelves	Dimension (mm)			HP	Voltage	Amps	Capacity Cu Ft. (L)	Net Weight lb (kg)	NEMA Config.
			L"	D"	H"						
<b>REFRIGERATION</b>											
C1-25GD	1	4	25.6 (650)	22.6 (580)	79.3 (2015)	1/4	115/60	2.88	14 (358)	291 (132)	5-15P
C1-28GD	1	4	26 (660)	25.6 (650)	80.2 (2040)	1/4+	115/60	2.88	13 (348)	320 (145)	5-15P

>> **Refrigeration Warranty:** 2 year parts and labour; 5 years on compressor; full details on page 226

Specifications subject to change without notice.



# Glass Door Merchandiser Refrigeration

C2-49GD



**C2-49GD**

**Features**



- Evaporator fan motor that stops when door is open to conserve energy
- Removable gasket that is easy to clean and replace
- Adjustable/removable plastic coated wire shelves - Shelves can be set-up to hold standard full size hotel pans
- Bottom-mounted cooling unit is easy to remove and clean
- Outstanding temperature preservation reduces energy consumption via foamed-in polyurethane cell insulation
- Auto evaporation of defrosting water
- Round corner design for inner bottom shelf to facilitate easy cleaning
- Cold air circulation via fan for temperature balance
- Refrigeration unit holds 33°F to 41°F (0.5°C to 5°C)

Merchandisers

Model	Doors	Shelves	Dimension (mm)			HP	Voltage	Amps	Capacity Cu Ft. (L)	Net Weight lb (kg)	NEMA Config.
			L"	D"	H"						
<b>REFRIGERATION</b>											
C2-49GD	2	10	48 (1220)	25.6 (650)	80.3 (2040)	1/2+	115/60	10.1	25 (708)	375 (170)	5-15P

>> **Refrigeration Warranty:** 2 year parts and labour; 5 years on compressor; full details on page 226



*Specifications subject to change without notice.*

# Glass Door Merchandiser Refrigeration

C3-78GD



Merchandisers

**C3-78GD**

**Features**

- Evaporator fan motor that stops when door is open to conserve energy
- Removable gasket that is easy to clean and replace
- Adjustable/removable plastic coated wire shelves - Shelves can be set-up to hold standard full size hotel pans
- Bottom-mounted cooling unit is easy to remove and clean
- Outstanding temperature preservation reduces energy consumption via foamed-in polyurethane cell insulation
- Auto evaporation of defrosting water
- Round corner design for inner bottom shelf to facilitate easy cleaning
- Cold air circulation via fan for temperature balance
- Refrigeration unit holds 33°F to 41°F (0.5°C to 5°C)

Model	Doors	Shelves	Dimension (mm)			HP	Voltage	Amps	Capacity Cu Ft. (L)	Net Weight lb (kg)	NEMA Config.
			L"	D"	H"						
<b>REFRIGERATION</b>											
C3-78GD	3	12	78.3 (1989)	29.9 (759.5)	80.9 (2055)	3/4	115/60	10.6	53 (1500)	704 (319.3)	5-15P

>> **Refrigeration Warranty:** 2 year parts and labour; 5 years on compressor; full details on page 226

*Specifications subject to change without notice.*





# Glass Door Merchandiser Refrigeration & Freezer

C2-48GD, C2-48GD-IS  
F2-48GD, F2-48GD-IS



**C2-48GD, C2-48GD-IS  
F2-48GD, F2-48GD-IS**

**Features**

- Black powder coated steel for exterior
- White coated aluminum or stainless steel interior walls
- Bottom mount compressor unit for easy maintenance
- LED lighting interior display system
- Easy to use digital temperature control
- 2 dual pane tempered glass with self closes swing doors
- Efficient refrigeration system
- Epoxy coated adjustable steel shelves, each hold up to 90 lbs of weight
- Refrigeration unit holds 33°F to 40°F (0.5°C to 4.5°C), freezer units hold -8°F to -1°F (-22°C to -18°C)
- Locked mounted glass doors to keep food safe
- Automatic defrosting system

Model	Doors	Shelves	Interior Walls	Dimension (mm)			HP	Voltage	Amps	Capacity Cu Ft. (L)	Net Weight lb (kg)	NEMA Config.
				L"	D"	H"						
<b>REFRIGERATION</b>												
C2-48GD	2	8	white coated aluminum	48 (1219)	31 (787.4)	83 (2108)	1/3	110/60	6.2	41.3 (1170)	423 (192)	5-15P
C2-48GD-IS	2	8	stainless steel	48 (1219)	31 (787.4)	83 (2108)	1/3	110/60	6.2	41.3 (1170)	423 (192)	5-15P
<b>FREEZER</b>												
F2-48GD	2	8	white coated aluminum	48 (1219)	31 (787.4)	83 (2108)	2/3	110/60	7	41.3 (1170)	454 (206)	5-15P
F2-48GD-IS	2	8	stainless steel	48 (1219)	31 (787.4)	83 (2108)	2/3	110/60	7	41.3 (1170)	454 (206)	5-15P

>> **Refrigeration Warranty:** 2 year parts and labour; 5 years on compressor; full details on page 226



Specifications subject to change without notice.

# Glass Door Merchandiser Freezers

F2-49GD



Merchandisers

**F2-49GD**

**Features**

- CABINET CONSTRUCTION
  - ° Exterior - coated steel
  - ° Interior - attractive, aluminum liner with stainless steel floor.
- Rounded corner design inside of the cabinet makes it easy to clean the inside storage room
- Triple pane thermal insulated glass door assembly with extruded aluminum frames
- R290 Refrigeration system holds -8°F to 0°F (-22°C to -18°C)
- Adjustable temperature set point and defrost frequency.
- Adjustable, heavy duty PVC coated shelves LED light
- "No stoop" lower shelf
- Easily accessible condenser coil for cleaning, and easy service access
- Simple installation with no plumbing required

Model	Doors	Shelves	Dimension (mm)			HP	Voltage	Amps	Capacity Cu Ft. (L)	Net Weight lb (kg)	NEMA Config.
			L"	D"	H"						
<b>FREEZER</b>											
F2-49GD	2	8	53.1 (1350)	31.8 (810)	82.7 (2102)	3/4	115/60	10.6	45 (1270)	441 (200)	5-15P

>> **Refrigeration Warranty:** 2 year parts and labour; 5 years on compressor; full details on page 226

*Specifications subject to change without notice.*



# Glass Door Merchandiser Refrigeration

C1-27.5GD



## C1-27.5GD

### Features

- Single glass door display fridge with ventilator cooling system
- LED interior lights
- Adjustable/removable plastic coated wire shelves
- Shelves can be set-up to hold standard full size hotel pans
- Bottom-mounted cooling unit is easy to remove and clean
- Outstanding temperature preservation reduces energy consumption via foamed-in polyurethane cell insulation
- Auto evaporation of defrosting water
- Round corner design for inner bottom shelf to facilitate easy cleaning
- Cold air circulation via fan for temperature balance
- Refrigeration unit holds 33°F to 45°F (0.5°C to 8°C) for optimum food preservation

Merchandisers

Model	Doors	Shelves	Dimension (mm)			HP	Voltage	Amps	Capacity Cu Ft. (L)	Net Weight lb (kg)	NEMA Config.
			L"	D"	H"						
<b>REFRIGERATION</b>											
C1-27.5GD	1	4	27.5 (700)	27.1 (690)	81 (2058)	1/2	115/60	9.5	21 (550)	238 (108)	5-15P

>> **Refrigeration Warranty:** 2 year parts and labour; 5 years on compressor; full details on page 226



Specifications subject to change without notice.

# Glass Door Merchandiser Refrigeration

C2S-45GD, C2S49GD  
C2S-52.4GD



**C2S-45GD, C2S-49GD  
C2S-52.4GD**

**Features**



- Double glass sliding door display fridge with ventilator cooling system
- LED interior lights
- Adjustable/removable plastic coated wire shelves
- Shelves can be set-up to hold standard full size hotel pans
- Bottom-mounted cooling unit is easy to remove and clean
- Outstanding temperature preservation reduces energy consumption via foamed-in polyurethane cell insulation
- Auto evaporation of defrosting water
- Round corner design for inner bottom shelf to facilitate easy cleaning
- Cold air circulation via fan for temperature balance
- Refrigeration unit holds 33°F to 45°F (0.5°C to 8°C) for optimum food preservation

Model	Doors	Shelves	Dimension (mm)			HP	Voltage	Amps	Capacity Cu Ft. (L)	Net Weight lb (kg)	NEMA Config.
			L"	D"	H"						
<b>REFRIGERATION</b>											
C2S-45GD	2	8	44.5 (1130)	31.5 (800)	79.5 (2020)	1/2	115/60	8.6	42 (1150)	375 (170)	5-15P
C2S-49GD	2	8	53.1 (1350)	37.8 (810)	79.3 (2014)	1/4+	115/60	4.32	45 (1274)	495 (225)	5-15P
C2S-52.4GD	2	8	52.4 (1330)	31.5 (800)	79.5 (2020)	1/2	115/60	9.5	50 (1400)	192 (178)	5-15P

>> **Refrigeration Warranty:** 2 year parts and labour; 5 years on compressor; full details on page 226

*Specifications subject to change without notice.*



# Countertop Refrigerator

C1-20GDCT-L  
C1-42GDCT-L



**C1-20GDCT-L  
C1-42GDCT-L**

**Features**

- Countertop series
- Glass design for maximum product visibility
- Attractive, black exterior with white interior
- Adjustable temperature
- LED interior lighting
- Shelves installed
- Lock installed
- Refrigeration unit holds 32°F to 50°F (0°C to 10°C) for optimum food preservation

Model	Dimension (mm) (inch)			Interior Dimensions (mm) (inch)			Voltage (V/Hz)	Amps	Capacity (L) (Cu Ft.)	Net Weight (kg) (lb)	Light box or not	NEMA Config.
	L	D	H	L	D	H						
<b>REFRIGERATION</b>												
C1-20GDCT-L	330	360	567	250	230	325	110/60	1.6	20	15	Yes	5-15P
	13	14.2	22.3	9.8	9	12.8			0.7	33		
C1-42GDCT-L	400	400	567	324	280	451	110/60	1.6	42	19	Yes	5-15P
	15.7	15.7	28.1	12.8	11	17.8			1.5	41.8		

>> **Refrigeration Warranty:** 2 year parts and labour; 5 years on compressor; full details on page 226



Specifications subject to change without notice.

# Countertop Refrigerator

C1-80GDCT-L  
C1-120GDCT-L



Merchandisers

**C1-80GDCT-L  
C1-120GDCT-L**

**Features**

- Countertop series
- Glass design for maximum product visibility;
- Attractive, black exterior with white interior
- Adjustable temperature
- LED interior lighting
- Shelves installed
- Lock installed
- Refrigeration unit holds 32°F to 50°F (0°C to 10°C) for optimum food preservation

Model	Dimension (mm) (inch)			Interior Dimensions (mm) (inch)			Voltage (V/Hz)	Amps	Capacity (L) (Cu Ft.)	Net Weight (kg) (lb)	Light box or not	NEMA Config.
	L	D	H	L	D	H						
<b>REFRIGERATION</b>												
C1-80GDCT-L	460	454	914	370	325	650	110/60	1.9	80	28	Yes	5-15P
	18.1	17.9	36	14.6	12.8	25.6			2.8	61.6		
C1-120GDCT-L	500	529	1032	420	400	757	110/60	2.2	120	36	Yes	5-15P
	19.7	20.8	40.6	16.5	15.7	29.8			4.2	79.2		

>> **Refrigeration Warranty:** 2 year parts and labour; 5 years on compressor; full details on page 226

Specifications subject to change without notice.



# Countertop Refrigerator

C1-21GDCT



**C1-21GDCT**

**Features**

- Countertop series
- Glass design for maximum product visibility
- Attractive, black exterior with white interior
- Adjustable temperaturee
- LED interior lighting
- Shelves installed
- Lock installed
- Refrigeration unit holds 32°F to 50°F (0°C to 10°C) for optimum food preservation

Model	Dimension (mm) (inch)			Interior Dimensions (mm) (inch)			Voltage (V/Hz)	Amps	Capacity (L) (Cu Ft.)	Net Weight (kg) (lb)	Light box or not	NEMA Config.
	L	D	H	L	D	H						
<b>REFRIGERATION</b>												
C1-21GDCT	330	410	474	240	276	168	110/60	1.6	20	15	No	5-15P
	13	16.4	18.7	9.4	10.9	6.6			0.7	33		

>> **Refrigeration Warranty:** 2 year parts and labour; 5 years on compressor; full details on page 226



Specifications subject to change without notice.

# Countertop Refrigerator

C1-68GDCT  
C1-98GDCT



Merchandisers

**C1-68GDCT**  
**C1-98GDCT**

**Features**

- Countertop series
- Glass design for maximum product visibility;
- Attractive, black exterior with white interior
- Adjustable temperature
- LED interior lighting
- Shelves installed
- Lock installed
- Refrigeration unit holds 32°F to 50°F (0°C to 10°C) for optimum food preservation



Model	Dimension (mm) (inch)			Interior Dimensions (mm) (inch)			Voltage (V/Hz)	Amps	Capacity (L) (Cu Ft.)	Net Weight (kg) (lb)	Light box or not	NEMA Config.
	L	D	H	L	D	H						
<b>REFRIGERATION</b>												
C1-68GDCT	435	498	678	355	370	361	110/60	1.9	68	25	No	5-15P
	17.1	19.6	26.7	14	14.6	14.2			2.4	55		
C1-98GDCT	470	472	836	406	361	534	110/60	1.9	98	31	No	5-15P
	18.5	18.6	32.9	16	14.2	21			3.5	68.2		

>> **Refrigeration Warranty:** 2 year parts and labour; 5 years on compressor; full details on page 226

Specifications subject to change without notice.





# Countertop Freezer

F1-20GDCT-L, F1-42GDCT-L  
F1-58GDCT-L



**F1-20GDCT-L, F1-42GDCT-L  
F1-58GDCT-L**

**Features**



- Countertop series
- Glass design for maximum product visibility
- Attractive, black exterior with white interior
- Adjustable temperature
- LED interior lighting
- Shelves installed
- Lock installed
- Refrigeration unit holds -13°F to 14°F (-25°C to -10°C) for optimum food preservation

Merchandisers

Model	Dimension (mm) (inch)			Interior Dimensions (mm) (inch)			Voltage (V/Hz)	Amps	Capacity (L) (Cu Ft.)	Net Weight (kg) (lb)	Light box or not	NEMA Config.
	L	D	H	L	D	H						
<b>FREEZER</b>												
F1-20GDCT-L	400	415	643	260	250	300	110/60	2.4	20	20	Yes	5-15P
	15.7	16.3	25.3	10.2	9.8	11.8			0.7	44		
F1-42GDCT-L	420	470	775	280	300	450	110/60	2.8	42	23	Yes	5-15P
	16.5	18.5	30.5	11	11.8	17.7			1.5	50.6		
F1-58GDCT-L	460	480	915	320	311	590	110/60	3.2	58	28	Yes	5-15P
	18.1	18.9	36	12.6	12.2	23.2			2	61.6		

>> **Refrigeration Warranty:** 2 year parts and labour; 5 years on compressor; full details on page 226



Specifications subject to change without notice.

# Countertop Freezer

F1-68GDCT-L  
F1-98GDCT-L



Merchandisers

**F1-68GDCT-L**  
**F1-98GDCT-L**

**Features**

- Countertop series
- Glass design for maximum product visibility
- Attractive, black exterior with white interior
- Adjustable temperature
- LED interior lighting
- Shelves installed
- Lock installed
- Refrigeration unit holds -13°F to 14°F (-25°C to -10°C) for optimum food preservation



Model	Dimension (mm / inch)			Interior Dimensions (mm / inch)			Voltage (V/Hz)	Amps	Capacity (L / Cu Ft.)	Net Weight (kg / lb)	Light box or not	NEMA Config.
	L	D	H	L	D	H						
<b>FREEZER</b>												
F1-68GDCT-L	590	570	835	455	405	295	110/60	4	68	46	Yes	5-15P
	23.4	22.4	32.9	17.9	15.9	11.6			2.4	101.2		
F1-98GDCT-L	595	570	955	455	405	415	110/60	4	98	50	Yes	5-15PP
	23.4	22.4	37.6	17.9	15.9	16.3			3.5	110		

>> **Refrigeration Warranty:** 2 year parts and labour; 5 years on compressor; full details on page 226

*Specifications subject to change without notice.*



# Countertop Refrigerator

C1-46GDCT, C1-75GDCT  
C1-90GDCT, C1-128GDCT



**C1-46GDCT, C1-75GDCT  
C1-90GDCT, C1-128GDCT**

**Features**

- Countertop series
- Glass design for maximum product visibility;
- Attractive, black exterior with white interior
- Adjustable temperature
- LED interior lighting
- Shelves installed
- Lock installed
- Refrigeration unit holds 39.2°F to 60.8°F (4°C to 16°C) for optimum food preservation

Merchandisers

Model	Dimension (mm (inch)			Voltage (V/Hz)	Amps	Capacity (L) (Cu Ft.)	Net Weight (kg) (lb)	Light box or not	NEMA Config.
	L	D	H						
<b>REFRIGERATION</b>									
C1-46GDCT	445	470	498	110/60	0.8	46	16.5	Yes	5-15P
	17.5	18.5	19.6						
C1-75GDCT	430	460	740	110/60	0.8	66	22.5	Yes	5-15P
	16.9	18.1	29.1						
C1-90GDCT	445	473	810	110/60	0.8	80	24.9	Yes	5-15P
	17.5	18.6	31.9						
C1-128GDCT	515	572	830	110/60	1.1	128	29.3	Yes	5-15P
	17.5	18.6	31.9						

>> **Refrigeration Warranty:** 2 year parts and labour; 5 years on compressor; full details on page 226



Specifications subject to change without notice.