



Equipment for the Foodservice Industry



Versa-Chill Refrigeration

by EFI



VERSA-CHILL SERIES

Reach-In Fridges & Freezers

C1-27VC
F1-27VC



**C1-27VC
F1-27VC**

Features

- Bottom-mounted cooling unit is easy to remove and clean
- Environmentally friendly R290 refrigerant
- Exterior & interior stainless steel construction
- Dixell digital temperature control system
- Heavy duty Embraco compressor
- Self-closing and stay open door
- Auto evaporation of defrosting water
- For optimum food preservation refrigeration units hold 33°F to 45°F (0.5°C to 8°C), freezer units hold -8°F to 1°F (-22°C to -18°C)
- Recessed door handles
- Safe lock for safe and secure use
- Removable gasket that is easy to clean and replace
- Adjustable/removable plastic coated wire shelves
- Shelves can be set-up to hold standard full size hotel pans
- Casters for easy movement

| Model | Doors | Shelves | Dimension (mm) | | | HP | Voltage | Amps | Capacity Cu Ft. (L) | Net Weight lb (kg) | NEMA Config. |
|----------------------|-------|---------|----------------|----------|-----------|-----|---------|------|------------------------|-----------------------|-----------------|
| | | | L" | D" | H" | | | | | | |
| REFRIGERATION | | | | | | | | | | | |
| C1-27VC-L | 1 | 3 | 28.7 (730) | 33 (840) | 85 (2160) | 1/6 | 115/60 | 2.1 | 19.1 (541) | 264 (120) | 5-15P |
| C1-27VC-R | 1 | 3 | 28.7 (730) | 33 (840) | 85 (2160) | 1/6 | 115/60 | 2.1 | 19.1 (541) | 264 (120) | 5-15P |
| FREEZER | | | | | | | | | | | |
| F1-27VC-L | 1 | 3 | 28.7 (730) | 33 (840) | 85 (2160) | 1/2 | 115/60 | 6.3 | 19.1 (541) | 264 (120) | 5-15P |
| F1-27VC-R | 1 | 3 | 28.7 (730) | 33 (840) | 85 (2160) | 1/2 | 115/60 | 6.3 | 19.1 (541) | 264 (120) | 5-15P |

>> **Refrigeration Warranty:** 2 year parts and labour; 5 years on compressor; full details on page 226

>> **Product Information:** Single door fridges can be purchased with right or left hinges, see product code for correct ordering

Specifications subject to change without notice.



VERSA-CHILL SERIES

Reach-In Fridges & Freezers

C2-39VC, C2-54VC
F2-39VC, F2-54VC



**C2-39VC, C2-54VC
F2-39VC, F2-54VC**

Features

- Bottom-mounted cooling unit is easy to remove and clean
- Environmentally friendly R290 refrigerant
- Exterior & interior stainless steel construction
- Dixell digital temperature control system
- Heavy duty Embraco compressor
- Self-closing and stay open door
- Auto evaporation of defrosting water
- For optimum food preservation refrigeration units hold 33°F to 45°F (1°C to 8°C), freezer units hold -8°F to 0.5°F (-22°C to -18°C)
- Recessed door handles
- Safe lock for safe and secure use
- Removable gasket that is easy to clean and replace
- Adjustable/removable plastic coated wire shelves
- Shelves can be set-up to hold standard full size hotel pans
- Casters for easy movement

| Model | Doors | Shelves | Dimension (mm) | | | HP | Voltage | Amps | Capacity Cu Ft. (L) | Net Weight lb (kg) | NEMA Config. |
|----------------------|-------|---------|----------------|----------|-----------|-----|---------|------|------------------------|-----------------------|-----------------|
| | | | L" | D" | H" | | | | | | |
| REFRIGERATION | | | | | | | | | | | |
| C2-39VC | 2 | 6 | 41.1 (1045) | 33 (840) | 85 (2160) | 1/3 | 115/60 | 3.2 | 30.2 (855) | 353 (160) | 5-15P |
| C2-54VC | 2 | 6 | 41.1 (1045) | 33 (840) | 85 (2160) | 1/3 | 115/60 | 3.2 | 44.8 (1268) | 408 (185) | 5-15P |
| FREEZER | | | | | | | | | | | |
| F2-39VC | 2 | 6 | 41.1 (1045) | 33 (840) | 85 (2160) | 3/4 | 115/60 | 8.6 | 30.2 (855) | 353 (160) | 5-15P |
| F2-54VC | 2 | 6 | 41.1 (1045) | 33 (840) | 85 (2160) | 3/4 | 115/60 | 8.6 | 44.8 (1268) | 408 (185) | 5-15P |

>> **Refrigeration Warranty:** 2 year parts and labour; 5 years on compressor; full details on page 226



Specifications subject to change without notice.

VERSA-CHILL SERIES

Reach-In Fridges & Freezers

C3-82VC
F3-82VC



**C3-82VC
F3-82VC**

Features

- Bottom-mounted cooling unit is easy to remove and clean
- Environmentally friendly R290 refrigerant
- Exterior & interior stainless steel construction
- Dixell digital temperature control system
- Heavy duty Embraco compressor
- Self-closing and stay open door
- Auto evaporation of defrosting water
- For optimum food preservation refrigeration units hold 33°F to 45°F (0.5°C to 8°C), freezer units hold -8°F to 1°F (-22°C to -18°C)
- Recessed door handles
- Safe lock for safe and secure use
- Removable gasket that is easy to clean and replace
- Adjustable/removable plastic coated wire shelves
- Shelves can be set-up to hold standard full size hotel pans
- Casters for easy movement

| Model | Doors | Shelves | Dimension (mm) | | | HP | Voltage | Amps | Capacity Cu Ft. (L) | Net Weight lb (kg) | NEMA Config. |
|----------------------|-------|---------|----------------|----------|-----------|-----|---------|------|------------------------|-----------------------|-----------------|
| | | | L" | D" | H" | | | | | | |
| REFRIGERATION | | | | | | | | | | | |
| C3-82VC | 3 | 9 | 83.7 (2125) | 33 (840) | 85 (2160) | 1/3 | 115/60 | 4.2 | 68 (1925) | 618 (280) | 5-15P |
| FREEZER | | | | | | | | | | | |
| F3-82VC | 3 | 9 | 83.7 (2125) | 33 (840) | 85 (2160) | 1 | 115/60 | 5.5 | 71 (2010) | 618 (280) | L14-20P |

>> **Refrigeration Warranty:** 2 year parts and labour; 5 years on compressor; full details on page 226

Specifications subject to change without notice.

