



Through meticulous design and technological innovation, Lamber has become a leader in the industry with dishwashing products that stand out aesthetically and for their functionality.

Their approach to manufacturing is a direct response to customer demand, blending sophisticated data processing techniques with human expertise. Product design, procurement of raw materials, assembly, testing, packaging, and shipment are all completed in-house, and to the highest of standards.

In 1948, Lamber made a commitment to delivering high-quality product and reliable services; the UNI EN ISO 9001 certification is a result of their continued dedication. Today, 80% of Lamber's production is exported internationally, providing the global market with avant-garde dishwashers adapted to the needs and desires of its vast clientele.



Distinguished by their reliability, cost efficiency and quality construction, Lamber dishwashers are built to withstand the demands of the busiest kitchens, leaving dishes sanitized after every cycle without the need for harsh chemicals. Reduced consumption of water and detergent provides significant savings, and skilled technical support for parts and services brings peace of mind.



Standard Features

- AISI 304 18/10 stainless steel construction inside & out
- Stainless steel wash and rinse arms (top & bottom)
- High temperature rinse cycles
- User-friendly control panel
- Water consumption as low as 0.5 gal/cycle (on most models)

Special Features

(Available on select models)

- Soft Start
- Multiple options for cycle duration
- Double wall thermal and acoustic insulation
- Interactive control panel with programmable wash parameters
- Energy Star Certification

Undercounter



Deluxe high-temperature undercounter dishwashers

Soft start • Soap and rinse pumps • Stainless steel upper and lower rotating wash and rinse arms
 • Removable control panel for easy maintenance • Automatic tank loading • Door opening safety device • Thermocontrol: guarantees accurate rinse temperature every cycle including during long-term, continuous use • Security thermostat

	F92EKDPS*	F92EKDPSAD	F92DYPS	DSP4DPS
Special features	Soft touch electronic control panel with temperature display. Double wall thermal and acoustic insulation	Auto-drain. Soft touch electronic control panel with temperature display. Double wall thermal and acoustic insulation	Electronic interactive control panel with programmable wash parameters, wash phase display, programmable rinse-aid doses and cycle counter. Double wall thermal and acoustic insulation	Wash and rinse temperature thermometers
Note	15 minute cycle ensures complete germ elimination	Special order. 50% non-refundable deposit required		
Drain type	Drain pump	Drain pump	Drain pump	Drain pump
Power	208-240V, 6650W, 29A	208-240V, 6650W, 29A	208-240V, 6650W, 29A	208-240V, 3650W, 15A
Plug	Hardwired	Hardwired	Hardwired	Hardwired
Included racks	1 x flat, 2 x dishes, 2 x cutlery inserts	1 x flat, 2 x dishes, 2 x cutlery inserts	1 x flat, 2 x dishes, 2 x cutlery inserts	1 x flat, 1 x dishes, 1 x cutlery insert
Wash cycle capacity	30 - 20 - 15 - 4 baskets/hr	30 - 20 - 15 - 4 baskets/hr	30 - 20 - 15 - 4 baskets/hr	30 baskets/hr
Clearance	12.5"	12.5"	12.5"	12"
Rack size (L x W)	20" x 20"	20" x 20"	20" x 20"	20" x 20"
Rinse temperature	179 - 194°F (82 - 90°C)	179 - 194°F (82 - 90°C)	179 - 194°F (82 - 90°C)	
Water consumption per cycle	0.63 Gal (2.4 L)	0.63 Gal (2.4 L)	0.63 Gal (2.4 L)	0.63 Gal (2.4 L)
Tank capacity	4.8 Gal (18.2 L)	4.8 Gal (18.2 L)	4.8 Gal (18.2 L)	4.8 Gal (18.2 L)
Inlet temp	131°F (55°C)	131°F (55°C)	131°F (55°C)	131°F (55°C)
Inlet size	3/4"	3/4"	3/4"	3/4"
Drain size	3/4"	3/4"	3/4"	3/4"
Cycle duration	2 - 3 - 4 - 15 mins.	2 - 3 - 4 - 15 mins.	2 - 3 - 4 - 15 mins.	2 mins.
Construction	Stainless steel 18/10 AISI 304	Stainless steel 18/10 AISI 304	Stainless steel 18/10 AISI 304	Stainless steel 18/10 AISI 304
Dimensions (L x W x H)	25.7" x 23.7" x 33"	25.7" x 23.7" x 33"	25.7" x 23.7" x 33"	25" x 24" x 32"
Net weight	152 lbs	152 lbs	170 lbs	137 lbs
Ship dim. (L x W x H)	45" x 32" x 47"	45" x 32" x 47"	45" x 32" x 47"	30" x 30" x 43"
Ship weight	225 lbs	225 lbs	225 lbs	160 lbs

*Warranty:
2 years parts and labor



Warranty:
1 year parts and labor
Made in Italy



F92EKDPS
&
F92EKDPSAD



F92DYPS



DSP4DPS

Glasswashers



High-temperature glasswashers

Soap and rinse pumps • Stainless steel lower rotating wash arm • Stainless steel upper and lower rotating rinse arms • Removable control panel for easy maintenance • Automatic tank loading • Door opening safety device • Thermocontrol: guarantees accurate rinse temperature every cycle including during long-term, continuous use • Security thermostat



DSP3



S480EKDPS

S480EKS

	DSP3	S480EKDPS	S480EKS
Special features	Wash and rinse temperature thermometers	Soft start. Soft touch electronic control panel with temperature display. Double wall thermal insulation	Soft start. Soft touch electronic control panel with temperature display. Double wall thermal insulation
Option		S480EKDPS 380V	
Drain type	Gravity drain	Drain pump	Gravity drain
Power	208-240V, 3200W, 15A ,	208-240V, 3200W, 15A ,	208-240V, 3200W, 15A ,
Plug	6-20P	6-20P	6-20P
Included racks	2 x glasses, 1 x saucer insert, 2 x cutlery insert	2 x glasses, 1 x saucer insert, 1 x cutlery insert	2 x glasses, 1 x saucer insert, 1 x cutlery insert
Wash cycle capacity	30 baskets/hr	60 - 30 - 20 baskets/hr	60 - 30 - 20 baskets/hr
Clearance	11.8"	12"	12"
Rack size (L x W)	16" x 16"	16" x 16"	16" x 16"
Rinse temperature	179 - 194°F (82 - 90°C)	179 - 194°F (82 - 90°C)	179 - 194°F (82 - 90°C)
Water consumption per cycle	0.63 Gal (2.4 L)	0.63 Gal (2.4 L)	0.63 Gal (2.4 L)
Tank capacity	4Gal (15L)	4.8 Gal (18.2 L)	4.8 Gal (18.2 L)
Inlet temp	131°F (55°C)	131°F (55°C)	131°F (55°C)
Inlet size	3/4"	3/4"	3/4"
Drain size	1-1/4"	3/4"	1-1/4"
Cycle duration	2 mins.	1 - 2 - 3 mins.	1 - 2 - 3 mins.
Construction	Stainless steel 18/10 AISI 304	Stainless steel 18/10 AISI 304	Stainless steel 18/10 AISI 304
Dimensions (L x W x H)	20" x 18" x 31"	20" x 19" x 29.25"	20" x 19" x 29.25"
Net weight	77 lbs	106 lbs	106 lbs
Ship dim. (L x W x H)	25" x 25" x 41"	47" x 43" x 32"	47" x 43" x 32"
Ship weight	120 lbs	135 lbs	135 lbs



Warranty:
1 year parts and labor
Made in Italy