WINE DRAWERS

by

Perlick®

WINEPcertified



- Deeper top drawer allows for upright storage of up to 30 open bottles*
- Lower drawer offers proper storage for up to 18 cradled bottles*
- Available in red and/or white wine temperature single-zone or dual-zone models

*based on 750 ml., 3-inch diameter bottles

DUAL-ZONE

BACK BAR REFRIGERATORS

- Available in 2-door (60") self-contained model
- Industry Exclusive wine drawers Deeper top drawer allows for upright storage of open bottles. Lower drawer provides additional storage for cradled bottles.
- Industry Exclusive full-extension wine shelves with stainless steel fronts
- All models are ANSI/NSF #7 approved for the storage and display of nonpotentially hazardous, bottled or canned products only, and are UL listed for the U.S. and Canada.
- Choice of temperature range; Refrigerator (34°F–42°F) or Wine (40°F–65°F). Factory set to approximately 38°F for Refrigerator, 45°F for White Wine and 60°F for Red Wine
- Wine Certified wine dispensing kit available



DZS60 Dual-Zone Wine Center w/ Wine Drawers and wine dispensing (shown)



DZS60 Dual-Zone Wine Center with stainless steel glass door, full-extension wine shelves and Wine Drawers (shown)



DZS60 - Dual-Zone Refrigerator with stainless steel glass door and wine dispensing (shown)

DZS60 (NSF) c (UL) us

Specifications







Exterior Length 60" (152.40 cm) **Exterior Depth** 24.75" (62.87 cm) Exterior Height 34.56" (87.78 cm) **Net Capacity** 7.4 cu. ft. (209.54L) **Number of Compartments** 2 Horsepower 1/5

Amps 2.5

R NEMA 5-15 Cord Plug Type (8' length)

Tapping Available Yes **Drawers Available** Yes

Electrical Supply 120 VAC/60 Hz/1 Ph

LED Light Options Crisp White™ or Cool Blue™

Solid (black, stainless, laminated, field laminated) Glass (black, stainless, laminated, field laminated) Drawers, Refrigerator (black, stainless, laminated, field laminated)

Drawers, Wine (black, stainless, laminated, field laminate)

Drawer Options

DUAL-ZONE WINE CENTER

The NEW Perlick Dual-Zone Wine Center (DZS36) has been specially designed to fit under a typical bar and features side-mounted refrigeration to reduce cabinet depth, making it a perfect fit for both new construction and retrofit applications. So even with limited space, your customers can capitalize on the growing demand for wine-by-the-glass.



DZS36 Series Self-Contained Dual-Zone





Temperature Range 40°F - 65°F [Choice of white wine factory setting (45°F) or red wine factory setting (60°F)]

Capacity Tapping compartment can fit two 1/6 slim kegs on each side.

- Features two compartments to prvide one digitally controlled temperature for white wines and another for reds.
- Available tapping kits feature WineCertified sanitary 304 stainless steel components to protect the delicate flavors of fine vintages.
- · Stainless Steel Door for Wine Dispensing



Our thinking on **illumination** has evolved.

LED lighting is now a standard feature on all new Perlick back bar refrigerators. Available in **Crisp White™** or **Cool Blue™**, these lights provide exceptional clarity and increase the visual impact of your stocked product.

- LED lighting is 50% more efficient*
- LED lighting has a 20% longer life*





(shown below)

* When compared to compact fluorescent bulbs



DUAL-ZONE WINE CENTER

INDUSTRY EXCLUSIVE Dual-zone wine center properly stores and dispenses wine.





DZS60 Wine Center with stainless steel glass door, full-extension shelves (left) and solid stainless door w/ single-faucet wine dispensing (right)





DZS60 Wine Center with Wine Drawers (left) and solid stainless door w/ single-faucet wine dispensing (right)

Now you can properly store and dispense wine at two separate temperatures in the same cabinet. Customize your dual-zone wine center with options to suit your specific needs:

- Wine drawers
- Solid doors with full-extension wine shelves
- Stainless glass doors with fullextension wine shelves
- 1-, 2-, 3-, 4- or 5-faucet wine tapping

eco/friendly



NARROW-DOOR

BACK BAR REFRIGERATORS

- Available in 1-, 2-, 3- or 4-door (32", 52", 72" or 92") self-contained models or 2-, 3- or 4-door (40", 60" or 80") remote models
- Narrow-door unit doors are 4" narrower than the standard unit to accommodate tight working spaces behind the bar
- All models are ANSI/NSF #7 approved for open food storage and are UL listed for the U.S. and Canada.
- Choice of temperature range; Refrigerator (34°F–42°F) or Wine (40°F–65°F). Factory set to approximately 38°F for Refrigerator, 45°F for White Wine and 60°F for Red Wine
- All refrigerator cabinets can be configured to accommodate tapping



BBSN32 – Refrigerator with solid stainless door (shown)



BBRN80 – Refrigerator with two (2) stainless glass doors, standard wire shelving and two (2) solid stainless doors (shown)

NARROW-DOOR

SELF-CONTAINED BACK BAR REFRIGERATORS



BBSN32 — Refrigerator with solid stainless steel door (shown)



BBSN52 – Refrigerator with stainless steel glass doors (2), standard wire shelving (shown)

BBSN32 (NSF) c (UL) us













Specifications Exterior Length 32" (81.28 cm) **Exterior Depth** 24.75" (62.87 cm)

Exterior Height 34.56" (87.78 cm) **Net Capacity** 6.0 cu. ft. (169.90 L)

Number of Compartments 1 Horsepower 1/6

Amps 1.8



NEMA 5-15 Cord Plug Type (8' length)

Tapping Available Yes **Drawers Available** No

> Electrical Supply 120 VAC/60 Hz/1 Ph or 230 VAC/50 Hz/1 Ph

LED Light Options Crisp White™ or Cool Blue™

Solid (black, stainless, laminated, field laminated) Glass (black, stainless, laminated, field laminated) BBSN52 (NSF) c (UL) us





R290 Refrigerant

Exterior Length 52" (132.08 cm) **Exterior Depth** 24.75" (62.87 cm) **Exterior Height** 34.56" (87.78 cm) **Net Capacity** 13.3 cu. ft. (376.61 L) **Number of Compartments** 2 Horsepower 1/5 **Amps** 2.5



NEMA 5-15 Cord Plug Type (8' length)

Tapping Available Yes **Drawers Available** No

Electrical Supply 120 VAC/60 Hz/1 Ph or 230 VAC/50 Hz/1 Ph

LED Light Options Crisp White™ or Cool Blue™

Door Options

Solid (black, stainless, laminated, field laminated) Glass (black, stainless, laminated, field laminated)



BBSN72 – Refrigerator with three (3) solid stainless steel glass doors (shown)



BBSN92 — Refrigerator with four (4) stainless steel glass doors (shown)

BBSN72 (NSF) c (UL) us





eco friendly R290 Refrigerant





eco friendly

Specifications

Exterior Length 72" (182.88 cm) **Exterior Depth** 24.75" (62.87 cm) **Exterior Height** 34.56" (87.78 cm) Net Capacity 20.6 cu. ft. (583.33 L) **Number of Compartments** 3 Horsepower 1/4 Amps 4.2



NEMA 5-15 Cord Plug Type (8' length)

Tapping Available Yes **Drawers Available** No Electrical Supply 120 VAC/60 Hz/1 Ph or 230 VAC/50 Hz/1 Ph

LED Light Options Crisp White™ or Cool Blue™

Door Options

Solid (black, stainless, laminated, field laminated) Glass (black, stainless, laminated, field laminated) BBSN92 (NSF) c (UL) us





R290 Refrigerant

Exterior Length 92" (233.68 cm) **Exterior Depth** 24.75" (62.87 cm) Exterior Height 34.56" (87.78 cm) Net Capacity 27.8 cu. ft. (787.21 L) **Number of Compartments** 4 Horsepower 1/4

Amps 4.2



REMA 5-15 Cord Plug Type (8' length)

Options

Tapping Available Yes **Drawers Available** No

Electrical Supply 120 VAC/60 Hz/1 Ph or 230 VAC/50 Hz/1 Ph

LED Light Options Crisp White™ or Cool Blue™

Door Options

Solid (black, stainless, laminated, field laminated) **Glass** (black, stainless, laminated, field laminated)

NARROW-DOOR

REMOTE BACK BAR REFRIGERATORS



BBRN40 – Refrigerator with two (2) stainless glass doors, standard wire shelving (shown)



BBRN60 – Refrigerator with three (3) solid stainless doors (shown)









BBRN40

Specifications

Door Options

Exterior Length 40" (101.60 cm) **Exterior Depth** 24.75" (62.87 cm) **Exterior Height** 34.56" (87.78 cm) **Net Capacity** 12.0 cu. ft. (339.80 L)

Number of Compartments 2 **Amps** 1.6

Electrical Connection Hard-wired

Evaporator Capacity - Remotes 1,900 Btu/Hr*

Tapping Available Yes **Drawers Available** No **Electrical Supply** 120 VAC/60 Hz/1 Ph or 230 VAC/50 Hz/1 Ph **LED Light Options** Crisp White[™] or Cool Blue[™]

Solid (black, stainless, laminated, field laminated) Glass (black, stainless, laminated, field laminated)

BBRN60





Exterior Length 60" (152.40 cm) **Exterior Depth** 24.75" (62.87 cm) **Exterior Height** 34.56" (87.78 cm) **Net Capacity** 19.0 cu. ft. (538.02 L) **Number of Compartments** 3 **Amps** 1.6 **Electrical Connection** Hard-wired **Evaporator Capacity – Remotes** 2,300 Btu/Hr*

Options **Tapping Available** Yes **Drawers Available** No Electrical Supply 120 VAC/60 Hz/1 Ph or 230 VAC/50 Hz/1 Ph **LED Light Options** Crisp White[™] or Cool Blue[™]

Door Options Solid (black, stainless, laminated, field laminated) **Glass** (black, stainless, laminate, field laminated)



BBRN80 — Refrigerator with two (2) stainless steel glass doors and two (2) solid stainless steel doors (shown)

BBRN80





Exterior Length 80" (203.20 cm) **Exterior Depth** 24.75" (62.87 cm) **Exterior Height** 34.56" (87.78 cm) **Net Capacity** 26.8 cu. ft. (758.89 L) Number of Compartments 4 **Amps** 2.5 **Electrical Connection** Hard-wired **Evaporator Capacity – Remotes** 2,300 Btu/Hr*

Tapping Available Yes **Drawers Available** No

Electrical Supply 120 VAC/60 Hz/1 Ph or 230

VAC/50 Hz/1 Ph

LED Light Options Crisp White[™] or Cool Blue[™]

Solid (black, stainless, laminated, field laminated) Glass (black, stainless, laminated, field laminated)

WHAT IS END-WALL **REFRIGERATION?**



Perlick's redesigned back bar refrigerators feature end-wall refrigeration, which increases cabinet capacity by 14%. All of the refrigeration components are confined to one compact module, which can be ordered with left or right placement on the cabinet.

From the leaders in wine storage and dispensing ...

Perlick WINE DISPENSING GUIDE



According to experts, wine enthusiasts are demanding a wider variety of high-end, wineby-the-glass choices from their favorite bars and restaurants.

Perlick's lineup of Wine **Certified storage and serving** products will help you capitalize on this growing trend in unique ways you won't see anywhere else in the industry.

> To learn more, check out our new Wine Storage and **Dispensing Guide to see** our entire line of Wine **Certifed products. Visit** perlick.com to download a copy today.



VINE Pcertified

SLIDING DOOR

BACK BAR REFRIGERATORS

- Available in 2- or 4-door (60" or 108") self-contained models or 2- or 4-door (48" or 96") remote models.
- Also available in pass-thru models (60" self-contained and 48" remote); see pages 31 and 33 for more information.
- Sliding doors are self-closing, and can be propped open for easy stocking
- All models are ANSI/NSF #7 approved for open food storage and are UL listed for the U.S. and Canada
- Choice of temperature range; Refrigerator (34°F–42°F) or Wine (40°F–65°F). Factory set to approximately 38°F for Refrigerator, 45°F for White Wine and 60°F for Red Wine



SDBS108 – Refrigerator with four (4) glass sliding doors, standard wire shelving (shown)



SDBR48 – Refrigerator with two (2) glass sliding doors, standard wire shelving (shown)

SLIDING DOOR

SELF-CONTAINED BACK BAR REFRIGERATORS



SDBS60 – Refrigerator with two (2) glass sliding doors, standard wire shelving (shown)



SDBS108 – Refrigerator with two (2) glass sliding doors, standard wire shelving (shown with **Cool Blue™** LED lighting)

SDBS60 (NSF) c (UL) us





eco friendly R290 Refrigerant





eco friendly

Exterior Length 60" (152.40 cm) **Exterior Depth** 24.75" (62.87 cm) **Exterior Height** 34.56" (87.78 cm) **Net Capacity** 14.8 cu. ft. (419.09 L) **Number of Compartments** 2 Horsepower 1/5 **Amps** 2.5



NEMA 5-15 Cord Plug Type (8' length)

Tapping Available No **Drawers Available** No **Electrical Supply** 120 VAC/60 Hz/1 Ph or 230 VAC/50 Hz/1 Ph **LED Light Options** Crisp White™ or Cool Blue™ SDBS108 (NSF) c (UL) us



R290 Refrigerant

Exterior Length 108" (274.32 cm) **Exterior Depth** 24.75" (62.87 cm) **Exterior Height** 34.56" (87.78 cm) **Net Capacity** 30.9 cu. ft. (874.99 L) **Number of Compartments** 4 Horsepower 1/4 **Amps** 4.2



NEMA 5-15 Cord Plug Type (8' length)

Options Tapping Available No **Drawers Available** No Electrical Supply 120 VAC/60 Hz/1 Ph or 230 VAC/50 Hz/1 Ph **LED Light Options** Crisp White™ or Cool Blue™

SLIDING DOOR

REMOTE BACK BAR REFRIGERATORS



SDBR48 – Refrigerator with two (2) glass sliding doors, standard wire shelving (shown)



SDBR96 – Refrigerator with four (4) glass sliding doors, standard wire shelving (shown)

SDBR48









Exterior Length 48" (121.92 cm) **Exterior Depth** 24.75" (62.87 cm) **Exterior Height** 34.56" (87.78 cm) **Net Capacity** 14.8 cu. ft. (419.09 L) Number of Compartments 2

Amps 2 **Electrical Connection** Hard-wired **Evaporator Capacity – Remotes** 2,300 Btu/Hr*

Tapping Available No **Drawers Available** No Electrical Supply 120 VAC/60 Hz/1 Ph or 230 VAC/50 Hz/1 Ph **LED Light Options** Crisp White™ or Cool Blue™

NSF c U us SDBR96

Exterior Length 96" (243.84 cm) **Exterior Depth** 24.75" (62.87 cm)

Exterior Height 34.56" (87.78 cm) **Net Capacity** 30.9 cu. ft. (874.99 L)

Number of Compartments 4

Amps 2

Electrical Connection Hard wired

Evaporator Capacity - Remotes 2,300 Btu/Hr*

Tapping Available No **Drawers Available** No

Electrical Supply 120 VAC/60 Hz/1 Ph or 230

VAC/50 Hz/1 Ph

LED Light Options Crisp White™ or Cool Blue™