

TAYLOR®

2021 Professional PRODUCTS



TOOLS THE PROS TRUST



The Taylor Advantage

Best Quality:

Precision measurement has been the exclusive focus of our business for 170 years. Our ability to fulfill the professional market's exacting standards for accuracy, durability, and design is built on a legacy of technical expertise, quality materials and a constant awareness of changing industry needs.

Best Selection:

The diversity of our product line reflects an ongoing commitment to provide the best solutions to the food service and professional community at every level... with ever-expanding choices in specialized temperature and weight measurement instruments that promote food safety, enhanced productivity and user convenience.

One Source:

We're the Food Service and Professional industry's most complete source for both thermometers and scales. So to simplify your purchasing process, plus improve your choices, quality and value... We've got everything you need. Taylor... Tools the Pros Trust in thermometers, timers, scales, professional cutlery, and kitchen gadgets.





Contents

Thermometers	4-31
Instant Read Dial Thermometers 1" Standard Grade	4-5
Instant Read Dial Thermometers 1" Superior Grade	5
Bi-Therm® Dial Thermometers 2" Superior Grade	6
Bi-Therm® Dial Thermometers 1 ¾" Superior Grade	6
Hand Held Thermocouple Thermometers	7
K-Type Probes for Thermocouple Thermometers	8
Infrared Thermometers	8-9
Pocket Digital Thermometers	9-11
Roast/Meat Thermometers	12
Cooking Thermometers	13
Candy & Deep Fry Thermometers	13-14
Oven/Grill Thermometers	15
Refrigerator/Freezer Thermometers	16-18
Panel Mount Digital Thermometer	18
Precision Thermometers	19-20
HACCP Food Safety Products	21
Special Use Thermometers/Strips	22-23
PH Meter and Accessories	24
Dial Thermometers/Clocks	24-25
Window/Wall Thermometers	26-27
Max/Min Thermometers	28
Pocket Case Thermometers	29
Thermometer Comparison Guide	30-31
Timers	32-37
Mechanical	32
Digital	33-35
Digital Timer Comparison Guide	36-37
Scales	38-47
Digital Scales	38
Digital Portion Control Scales	39-42
Compact Analog Portion Control Scales	42
Analog Portion Control Scales	42-43
Heavy Duty Mechanical Scales	44
Receiving Scales	45
Scale Comparison Guide	46-47
Cutlery	48-51
Chef'n Kitchen Tools & Gadgets	52-53
Fruit & Veg Prep	52-53
Switchit® Spatulas	53
Wine & Bar Accessories	54-55
Manual Corkscrews	54
Preservers	55
Other Accessories	55
Hotel & Resort	56-57
Miscellaneous Parts, Supplies & Accessories	58
Terms and Conditions	58
Index	59-61
Notes	62-63

THERMOMETERS

Instant Read Dial Thermometers 1" Standard Grade



- ▶ 5" stem
- ▶ Recalibratable
- ▶ Accuracy +/- 2°F/1°C at dial midpoint
- ▶ Patented recalibration wrench built into pocket case
- ▶ Shatterproof Lexan® plastic lens
- ▶ High visibility dial graphics
- ▶ Convenient, protective case
- ▶ Durable stainless steel
- ▶ Superior shock protection
- ▶ Individual cartons with hang tabs (except 3621N, 5988N, 5989NFS which are a blister card)



Exclusive Safe-T-Set Calibration System

All 1" models have a protective pocket case which doubles as a calibration tool.



3621N

- ▶ Temperature range: 0°F /220°F
- ▶ Safe-T-Guard™ case incorporates an EPA registered product that inhibits the growth of bacterial odor and mold on the product case

UPC	PACK QTY.	U of M
0 77784 03621 1	6	1 ea.

5988N

- ▶ Temperature range: 50°F /550°F

UPC	PACK QTY.	U of M
0 77784 05988 3	6	1 ea.

5989NFS

- ▶ Temperature range: 0°F /220°F and -14°C/105°C

UPC	PACK QTY.	U of M
0 77784 03157 5	6	1 ea.

6065N

- ▶ Temperature range: -40°C /70°C

UPC	PACK QTY.	U of M
0 77784 60650 6	12	1 ea.

6091N

- ▶ Temperature range: -40°F /120°F

UPC	PACK QTY.	U of M
0 77784 06091 9	12	1 ea.

6092N

- ▶ Temperature range: 0°F /220°F

UPC	PACK QTY.	U of M
0 77784 60921 7	12	1 ea.

6093N

- ▶ Temperature range: 50°F /550°F

UPC	PACK QTY.	U of M
0 77784 06093 3	12	1 ea.

6094N

- ▶ Temperature range: -40°C /50°C

UPC	PACK QTY.	U of M
0 77784 06094 0	12	1 ea.

6096N

- ▶ Temperature range: -40°F /160°F

UPC	PACK QTY.	U of M
0 77784 06096 4	12	1 ea.

6099N

- ▶ Temperature range: -10°C /110°C

UPC	PACK QTY.	U of M
0 77784 06099 5	12	1 ea.

Instant Read Dial Thermometers 1 3/4" Standard Grade




- ▶ 5" stem and 1 3/4" dial
- ▶ Recalibratable
- ▶ Standard grade with 1 point calibration
- ▶ Safe-T-Guard™ case incorporates an EPA registered product that inhibits the growth of bacterial odor and mold on the product case



8018N

- ▶ Temperature range: 0°F/220°F and 0°C/100°C

UPC	PACK QTY.	U of M
	6	1 ea.


Instant Read Dial Thermometers 1" Superior Grade



- ▶ 5" stem
- ▶ Recalibratable
- ▶ Accuracy +/- 2°F/1°C of entire range
- ▶ 3 point calibration
- ▶ Patented recalibration wrench built into pocket case
- ▶ Shatterproof Lexan® plastic lens
- ▶ High visibility dial graphics
- ▶ Convenient protective case
- ▶ Durable stainless steel
- ▶ Superior shock protection
- ▶ Individual cartons with hang tabs


6071

- ▶ Temperature range: -40°F /120°F

UPC	PACK QTY.	U of M
	12	1 ea.


6072N

- ▶ Temperature range: 0°F/220°F

UPC	PACK QTY.	U of M
	12	1 ea.


6073J

- ▶ Temperature range: 50°F /550°F

UPC	PACK QTY.	U of M
	12	1 ea.


6075

- ▶ Temperature range: 25°F /125°F

UPC	PACK QTY.	U of M
	12	1 ea.


6076J

- ▶ Temperature range: -40°F /160°F

UPC	PACK QTY.	U of M
	12	1 ea.

6079J

- ▶ Temperature range: -10°C /110°C

UPC	PACK QTY.	U of M
	12	1 ea.

THERMOMETERS

Bi-Therm® Dial Thermometers 2" Superior Grade



- ▶ 8" stems
- ▶ Recalibratable
- ▶ 3 point calibration
- ▶ Accuracy +/- 2°F/1°C of entire range
- ▶ Stainless steel external parts
- ▶ High visibility dial graphics
- ▶ Extended scale design
- ▶ Packed in individual boxes

Model	UPC	PACK QTY.	U of M
6211J ▶ Temperature range: -40°F /120°F		1	1 ea.
6212J ▶ Temperature range: 25°F /125°F		1	1 ea.
6215J ▶ Temperature range: 0°F /220°F		1	1 ea.
6220J ▶ Temperature range: 50°F /550°F		1	1 ea.
6235J ▶ Temperature range: -10°C /110°C		4	1 ea.

Bi-Therm® Dial Thermometers 1¾" Superior Grade



- ▶ 8" stems
- ▶ Recalibratable
- ▶ 3 point calibration
- ▶ Accuracy +/- 2°F/1°C of entire range
- ▶ Stainless steel external parts
- ▶ High visibility dial graphics
- ▶ Anti-parallax dial/case design
- ▶ Extended scale design
- ▶ Superior shock protection
- ▶ Packed in individual boxes (except 8215N is on blister card)

Model	UPC	PACK QTY.	U of M
8212J ▶ Temperature range: 25°F /125°F		1	1 ea.
8215N ▶ Temperature range: 0°F /220°F and -10°C /110°C ▶ Vessel clip included		6	1 ea.
8220J ▶ Temperature range: 50°F /550°F		1	1 ea.
8238J ▶ Temperature range: 0°C /250°C ▶ 2°C divisions		1	1 ea.



Hand Held Thermocouple Thermometers



9306N Splash-Proof Dual Temp Infrared Thermometer with Fold Out Thermocouple Step Down Probe

- ▶ Thermocouple range: -67°/626°F and -55°/330°C with accuracy from 14° to 149°F (-10° to 65°C) +/- 1°F (0.6°C)
- ▶ Infrared range: -67°/482°F and -55°/250°C with accuracy from 32°F to 149°F (0°C to 65°C) +/- 2°F (1°C)
- ▶ Resolution: 0.5°F or 0.2°C
- ▶ HACCP pass/fail light system
- ▶ Min/max/hold features
- ▶ Adjustable emissivity
- ▶ D:S=3:1
- ▶ Auto shut off
- ▶ IP65 rated
- ▶ 2 - AAA batteries included

UPC	PACK QTY.	U of M
0 77784 09306 1	2	1 ea.



9405 High Accuracy Waterproof K-Type Thermocouple Thermometer

- ▶ Temperature range: -40°F /500°F and -40°C/260°C
- ▶ With a 2-second response probe and a 4 ft. cord
- ▶ +/- 1° over HACCP range
- ▶ Recalibratable from the front panel switches
- ▶ Auto-off feature
- ▶ IP65 rated
- ▶ 1 - 9V battery included

UPC	PACK QTY.	U of M
0 77784 09405 1	24	1 ea.



9821PBN Thermocouple Thermometer with Step Down K-Type Probe

- ▶ Temperature range: -58°F /392°F and -50°C/200°C
- ▶ Compact size with oversized 1.1" LCD readout
- ▶ Hold function and C/F switch
- ▶ Includes 1.5mm step down k-type probe with quick response time
- ▶ IP65 rated
- ▶ 2 - AAA batteries included

UPC	PACK QTY.	U of M
0 77784 02886 5	2	1 ea.



9867FDA Digital Folding Probe Thermometer

- ▶ Temperature range: -40°F /572°F and -40°C/300°C
- ▶ 1.5mm step down probe diameter, FDA recommended
- ▶ Safe-T-Guard™ case incorporates an EPA registered product that inhibits the growth of bacterial odor and mold on the product case
- ▶ Recalibration system
- ▶ Thermocouple
- ▶ stabilized reading in 5 seconds or less
- ▶ 2 - AAA batteries included

UPC	PACK QTY.	U of M
0 77784 09867 7	2	1 ea.



9868FDA Folding Thermocouple Thermometer ★

- ▶ Temperature range: -40°F /572°F and -40°C/300°C
- ▶ 1.5mm step down probe diameter, FDA recommended
- ▶ Pivoting probe of 270°
- ▶ Large 180° rotating display with blue backlight
- ▶ Recalibratable with auto off and hold features
- ▶ Safe-T-Guard™ case incorporates an EPA registered product that inhibits the growth of bacterial odor and mold on the product case
- ▶ Black nylon storage case
- ▶ Waterproof IP67 rated

UPC	PACK QTY.	U of M
0 77784 03351 7	2	1 ea.



5256860 Folding Thermocouple Thermometer ★

- ▶ Temperature range: -40°F /572°F and -40°C/300°C
- ▶ 1.5mm step down probe diameter, FDA recommended
- ▶ Pivoting probe of 270°
- ▶ Large 180° rotating display with blue backlight
- ▶ Recalibratable with auto off and hold features
- ▶ Safe-T-Guard™ case incorporates an EPA registered product that inhibits the growth of bacterial odor and mold on the product case
- ▶ Black nylon storage case
- ▶ Waterproof IP67 rated

UPC	PACK QTY.	U of M
0 77784 03614 3	2	1 ea.

THERMOMETERS

K-Type Probes for Thermocouple Thermometers



9806 Clip-On Probe

- ▶ Clip-on oven probe includes 4' lead

UPC	PACK QTY.	U of M
	1	1 ea.



98102 Hamburger/Filet Probe

- ▶ 3/16" tip with 5' lead

UPC	PACK QTY.	U of M
	1	1 ea.



9812 Angle Surface Probe

- ▶ Includes 5' lead

UPC	PACK QTY.	U of M
	1	1 ea.



9818 Step-Down Penetration Probe with 3' Lead

- ▶ 1.50 mm tip diameter with 3' lead

UPC	PACK QTY.	U of M
	1	1 ea.



Infrared Thermometers



CR2032 BATTERY INCLUDED
 HOLD
 °F/°C
 FAHRENHEIT/CELSIUS

9305 Dual Temp Infrared & Thermocouple Thermometer

- ▶ Thermocouple range: -67°F /630°F and -55°C/330°C
- ▶ Infrared range: -27°F /428°F and -33°C/220°C
- ▶ Great for non-contact measurement
- ▶ Min/max/hold features
- ▶ Includes folding step down probe with nylon storage case
- ▶ 1 - CR2032 battery included

UPC	PACK QTY.	U of M
	2	1 ea.



AAA BATTERY INCLUDED
 °F/°C
 FAHRENHEIT/CELSIUS

9523 Infrared Thermometer

- ▶ Temperature range: -49°F /752°F and -45°C/400°C
- ▶ Scan and hold features
- ▶ Emissivity fixed at 0.95 and resolution at 0.1°F/0.1°C
- ▶ Spot to distance ratio is 6:1
- ▶ Includes nylon storage case
- ▶ 2 - AAA batteries included

UPC	PACK QTY.	U of M
	2	1 ea.



CR2032 BATTERY INCLUDED

9526 Mini Infrared Thermometer

- ▶ Temperature range: -27°F /390°F
- ▶ In °F scale only
- ▶ Compact and easy to scan
- ▶ Auto-off feature
- ▶ Spot to distance ratio is 1:1
- ▶ Resolution 0.5°
- ▶ 1 - CR2032 battery included

UPC	PACK QTY.	U of M
	6	1 ea.

Infrared Thermometers (cont.)



CR2032 °F/°C
BATTERY INCLUDED FAHRENHEIT/CELSIUS

9527 Infrared Thermometer

- ▶ Temperature range: -67°F /428°F and -55°C/220°C with accuracy of +/- 1.1°F (0.6°C)
- ▶ Resolution: 0.1°F/°C
- ▶ Min/max/lock modes
- ▶ Auto-off after 15 seconds
- ▶ Emissivity range is 0.95 (default) and adjustable to 0.005 to 1 (step 0.1)
- ▶ Quick response at 1 second
- ▶ Low battery indicator
- ▶ Protective rubber boot and lanyard included
- ▶ 1 - CR2032 battery included

UPC	PACK QTY.	U of M
0 77784 09527 0	2	1 ea.



9V °F/°C BACKLIGHT
BATTERY INCLUDED FAHRENHEIT/CELSIUS

5256881 Infrared Thermometer ★

- ▶ Temperature range: -58°F/716° and -50°C/380°C
- ▶ Scan and hold features
- ▶ Emissivity fixed at 0.95 and resolution at 0.1°F/0.1°C
- ▶ Spot to distance ratio is 12:1
- ▶ 1 - 9V battery included

UPC	PACK QTY.	U of M
0 77784 03617 4	2	1 ea.



Pocket Digital Thermometers



LR44 °F/°C MAGNETIC NSF
BATTERY INCLUDED FAHRENHEIT/CELSIUS

1476FDA Compact Folding Thermometer

- ▶ Temperature range: -40°F /392°F and -40°C/200°C
- ▶ FDA recommended step down probe
- ▶ Auto-off feature
- ▶ Magnet on the back
- ▶ Lanyard included
- ▶ 1 - LR44 battery included

UPC	PACK QTY.	U of M
0 77784 02531 4	6	1 ea.



MULTIUSE INSTANT READ DIGITAL DISPLAY LR44 NSF
BATTERY INCLUDED FAHRENHEIT/CELSIUS

3516FS Digital Instant Read Thermometer

- ▶ Temperature range: -40°F /302°F
- ▶ Available in °F scale only
- ▶ 0.4" LCD readout
- ▶ Protective pocket sleeve
- ▶ 1 - LR44 battery included

UPC	PACK QTY.	U of M
0 77784 03123 0	6	1 ea.



LR44 °F/°C NSF
BATTERY INCLUDED FAHRENHEIT/CELSIUS

3519FDA Waterproof Digital Instant Read Thermometer with Step Down Probe

- ▶ Temperature range: -40°F /450°F and -40°C/232°C
- ▶ Resolution: 0.1°F/°C
- ▶ Easy to grip, pen style design
- ▶ 1.5mm step down probe as recommended by the FDA
- ▶ Waterproof design with instant read and hold feature
- ▶ Auto-shut off feature
- ▶ 1 - LR44 battery included

UPC	PACK QTY.	U of M
0 77784 02509 3	3	1 ea.


THERMOMETERS

Pocket Digital Thermometers (cont.)



3519PRFDA Waterproof Digital Instant Read Thermometer with Step Down Probe


- ▶ Temperature range: -40°F /450°F and -40°C/230°C
- ▶ Resolution: 0.1°F/C
- ▶ Easy to grip, pen style design
- ▶ 1.5mm step down probe as recommended by the FDA
- ▶ Waterproof design with instant read and hold feature
- ▶ Auto-shut off feature
- ▶ Helps support allergy safety
- ▶ 1 - LR44 battery included

UPC	PACK QTY.	U of M
	3	1 ea.



9836 Adjustable Head Digital Thermometer


- ▶ Temperature range: -40°F /450°F and -40°C/230°C
- ▶ Supersized 1.0" readout
- ▶ Head pivots in multiple positions for easier reading
- ▶ Durable stainless steel 5" stem with step down tip
- ▶ Storage sleeve
- ▶ Auto-shut off feature
- ▶ 1 - LR44 battery included

UPC	PACK QTY.	U of M
	6	1 ea.



9840PRN Digital Thermometer

- ▶ Temperature range: -40°F /302°F and -40°C/150°C
- ▶ Reduces the risk of cross-contamination
- ▶ Helps support allergy safety
- ▶ Stainless steel step down probe
- ▶ Auto-off feature
- ▶ Protective sleeve included
- ▶ 1 - LR44 battery included

UPC	PACK QTY.	U of M
	6	1 ea.



9840RB Digital Thermometer


- ▶ Temperature range: -40°F /302°F and -40°C/150°C
- ▶ Protective rubber boot included to withstand drops
- ▶ Stainless steel step down probe
- ▶ Auto-off feature
- ▶ Protective sleeve included
- ▶ 2 - LR44 batteries included

UPC	PACK QTY.	U of M
	6	1 ea.



9841RB High Temp Digital Thermometer


- ▶ Temperature range: -40°F /500°F and -40°C/260°C
- ▶ Protective rubber boot included to withstand drops
- ▶ Stainless steel step down probe
- ▶ Auto-off feature
- ▶ Protective sleeve included
- ▶ 2 - LR44 batteries included

UPC	PACK QTY.	U of M
	6	1 ea.




9842FDA Waterproof Digital Thermometer

- ▶ Temperature range: -40°F /450°F and -40°C/232°C
- ▶ Auto-off feature
- ▶ Recalibratable and C/F switch
- ▶ Safe-T-Guard™ case incorporates an EPA registered product that inhibits the growth of bacterial odor and mold on the product case
- ▶ 1 - LR44 battery included

UPC	PACK QTY.	U of M
	6	1 ea.

Pocket Digital Thermometers (cont.)



9848EFDA Waterproof Digital Thermometer

- ▶ Temperature range: -40°F /450°F and -40°C/232°C
- ▶ Waterproof and dishwasher safe
- ▶ Min/max/hold features
- ▶ Recalibratable
- ▶ Safe-T-Guard™ case incorporates an EPA registered product that inhibits the growth of bacterial odor and mold on the product case
- ▶ Blue backlit LCD
- ▶ Lanyard included
- ▶ 1 - CR2032 battery included

UPC	PACK QTY.	U of M
0 77784 00335 4	6	1 ea.



9867FDA Digital Folding Probe Thermometer

- ▶ Temperature range: -40°F /572°F and -40°C/300°C
- ▶ 1.5mm step down probe diameter, FDA recommended
- ▶ Safe-T-Guard™ case incorporates an EPA registered product that inhibits the growth of bacterial odor and mold on the product case
- ▶ Recalibration system
- ▶ Thermocouple
- ▶ Stabilized reading in 5 seconds or less
- ▶ 2 - AAA batteries included

UPC	PACK QTY.	U of M
0 77784 09867 7	2	1 ea.



9868FDA Folding Thermocouple Thermometer ★

- ▶ Temperature range: -40°F /572°F and -40°C/300°C
- ▶ 1.5mm step down probe diameter, FDA recommended
- ▶ Pivoting probe of 270°
- ▶ Large 180° rotating display with white backlight
- ▶ Recalibratable with auto off and hold features
- ▶ Safe-T-Guard™ case incorporates an EPA registered product that inhibits the growth of bacterial odor and mold on the product case
- ▶ Black nylon storage case
- ▶ Waterproof IP67 rated

UPC	PACK QTY.	U of M
0 77784 03351 7	2	1 ea.



5256860 Folding Thermocouple Thermometer ★

- ▶ Temperature range: -40°F /572°F and -40°C/300°C
- ▶ 1.5mm step down probe diameter, FDA recommended
- ▶ Pivoting probe of 270°
- ▶ Large 180° rotating display with white backlight
- ▶ Recalibratable with auto off and hold features
- ▶ Safe-T-Guard™ case incorporates an EPA registered product that inhibits the growth of bacterial odor and mold on the product case
- ▶ Black nylon storage case
- ▶ Waterproof IP67 rated

UPC	PACK QTY.	U of M
0 77784 03614 3	2	1 ea.



9877FDA Compact Waterproof Digital Thermometer

- ▶ Temperature range: -40°F /450°F and -40°C/232°C
- ▶ Waterproof and dishwasher safe
- ▶ 1.5mm step down probe diameter, FDA recommended
- ▶ Response time less than 6 seconds with 1 second updates
- ▶ Min/max/hold features
- ▶ Safe-T-Guard™ case incorporates an EPA registered product that inhibits the growth of bacterial odor and mold on the product case
- ▶ Auto-off feature
- ▶ 1 - CR1225 battery included

UPC	PACK QTY.	U of M
0 77784 98770 4	6	1 ea.



9878E High Precision Waterproof Digital Thermometer

- ▶ Temperature range: -40°F /500°F and -40°C/260°C
- ▶ Waterproof and dishwasher safe
- ▶ 1.5 mm step down probe diameter, FDA recommended
- ▶ Min/max/hold features
- ▶ Recalibratable
- ▶ Safe-T-Guard™ case incorporates an EPA registered product that inhibits the growth of bacterial odor and mold on the product case
- ▶ Auto-off and disable auto-off functions
- ▶ Amber backlit LCD
- ▶ 1 - CR2032 battery included

UPC	PACK QTY.	U of M
0 77784 09878 3	3	1 ea.

THERMOMETERS

Roast/Meat Thermometers



9878EPR Allergen Waterproof Digital Pocket Thermometer

- ▶ Temperature range: -40°F /500°F and -40°C/260°C
- ▶ Waterproof and dishwasher safe
- ▶ Helps support allergy safety
- ▶ 1.5mm step down probe diameter, FDA recommended
- ▶ Min/max/hold features
- ▶ Recalibratable
- ▶ Safe-T-Guard™ case incorporates an EPA registered product that inhibits the growth of bacterial odor and mold on the product case
- ▶ Auto-off and disable auto-off functions
- ▶ Amber backlit LCD
- ▶ 1 - CR2032 battery included

UPC	PACK QTY.	U of M
	3	1 ea.



3504 Meat Dial Thermometer

- ▶ Temperature range: 120°F to 210°F
- ▶ 2" dial with USDA guidelines
- ▶ Adjustable temperature indicator
- ▶ Stainless steel 4½" stem

UPC	PACK QTY.	U of M
	6	1 ea.



5937N Multi-Purpose Thermometer

- ▶ Temperature range: 105°F to 185°F
- ▶ Armored sabre-tipped tube for easy piercing
- ▶ Meat and yeast temperature guides
- ▶ Dishwasher safe

UPC	PACK QTY.	U of M
	6	1 ea.



5939N Meat Thermometer

- ▶ Temperature range: 120°F to 212°F
- ▶ Large 3" dial
- ▶ Slide temperature indicator
- ▶ Meat guidelines on dial

UPC	PACK QTY.	U of M
	6	1 ea.



61054J Meat Thermometer

- ▶ Temperature range: 0°F to 220°F
- ▶ Easy to read 2" dial
- ▶ 4" stainless steel stem with glass crystal
- ▶ Packed in individual carton

UPC	PACK QTY.	U of M
	1	1 ea.



5984J Instant Read Meat Thermometer

- ▶ Temperature range: 0°F /220°F
- ▶ 1¼" dial with 5" stem
- ▶ Recalibratable

UPC	PACK QTY.	U of M
	1	1 ea.

Cooking Thermometers



5933 Floating Thermometer

- ▶ Temperature range: 120°F to 220°F
- ▶ Floats for use in any soups, sauces, stews
- ▶ Sealed housing, temperature and food safe stainless steel construction
- ▶ 4 key temperature range indicators on dial

UPC	PACK QTY.	U of M
0 77784 05933 3	6	1 ea.



1470FS Digital Thermometer and Timer

- ▶ Temperature range: 32°F /392°F and 0°C/200°C
- ▶ Sealed stainless steel probe with 4' cord
- ▶ Temperature alarm signals when food is done
- ▶ 1.5mm step down probe diameter, FDA recommended
- ▶ Non-slip nylon clip on probe to prevent moisture from entering the probe
- ▶ On/off switch to preserve battery life
- ▶ Folds down for compact storage
- ▶ Magnet on back for mounting to stove
- ▶ 2 - AAA batteries included

UPC	PACK QTY.	U of M
0 77784 02606 9	6	1 ea.



1470FSRP Replacement Probe for Model 1470FS

- ▶ Replacement Probe for Model 1470FS and 1470N
- ▶ Sealed stainless steel probe with 4' cord

UPC	PACK QTY.	U of M
0 77784 02651 9	1	1 ea.

Candy & Deep Fry Thermometers



3505 Candy/Deep Fry Thermometer

- ▶ Temperature range: -40°F /450°F and -40°C/230°C
- ▶ 2" dial with candy zones
- ▶ Adjustable pan/kettle clip
- ▶ Temperature indicator
- ▶ 6" stem

UPC	PACK QTY.	U of M
0 77784 03505 4	6	1 ea.



3522FS Deep Fry Thermometer

- ▶ Temperature range: 50°F /550°F and 50°C/285°C
- ▶ 1 3/4" dial
- ▶ Durable 12" stainless steel stem with adjustable pan clip
- ▶ Temperature indicator

UPC	PACK QTY.	U of M
0 77784 03122 3	6	1 ea.



5911N Candy/Deep Fry Thermometer

- ▶ Temperature range: 100°F /400°F and 50°C/200°C
- ▶ Large 3" dial
- ▶ Slide temperature indicator
- ▶ Durable rounded tip
- ▶ 6" stainless steel stem
- ▶ Candy zones on dial

UPC	PACK QTY.	U of M
0 77784 05911 1	6	1 ea.

THERMOMETERS


Candy & Deep Fry Thermometers (cont.)



MULTIUSE
°F/°C
FAHRENHEIT/
CELSIUS

5978N Candy/Deep Fry Thermometer

- ▶ Temperature range: 100°F / 400°F and 50°C / 200°C
- ▶ Glass tube with adjustable pan clip
- ▶ Protective storage sleeve is printed with convenient cooking chart
- ▶ 8" in length

UPC	PACK QTY.	U of M
	6	1 ea.




MULTIUSE
°F/°C
FAHRENHEIT/
CELSIUS

STAINLESS
STEEL

5983N Candy/Deep Fry Thermometer

- ▶ Temperature range: 100°F / 400°F and 50°C / 200°C
- ▶ Insulated handle with built in pan clip
- ▶ Large printing for easy to read temperature zones
- ▶ Classic stainless steel design
- ▶ 12" in length


UPC	PACK QTY.	U of M
	6	1 ea.



STAINLESS
STEEL

6084J8 Professional Candy/Deep Fry Thermometer

- ▶ Temperature range: 50°F / 550°F
- ▶ 2" dial with 8" stem

UPC	PACK QTY.	U of M
	50	1 ea.



STAINLESS
STEEL

6084J12 Professional Candy/Deep Fry Thermometer

- ▶ Temperature range: 50°F / 550°F
- ▶ 2" dial with 12" stem

UPC	PACK QTY.	U of M
	1	1 ea.




STAINLESS
STEEL

°F/°C
FAHRENHEIT/
CELSIUS

BATTERY
INCLUDED

983915 Adjustable Head Digital Candy/Deep Fry Thermometer

- ▶ Temperature range: -40°F / 450°F and -40°C / 230°C
- ▶ Multi-position pivoting head
- ▶ Large 1" LCD readout
- ▶ Adjustable pan clip
- ▶ Durable stainless steel 9" stem
- ▶ Auto-off feature
- ▶ 1 - LR44 battery included

UPC	PACK QTY.	U of M
	3	1 ea.



Oven/Grill Thermometers



814GW Smoker Thermometer

- ▶ Temperature range: 100°F / 475°F
- ▶ Mounts directly onto smoker
- ▶ Luminescent ink for easy low-light viewing

UPC	PACK QTY.	U of M
0 77784 02840 7	6	1 ea.



5921N Professional Hot Holding Thermometer

- ▶ Temperature range: 100°F / 180°F and 38°C / 82°C
- ▶ Dial includes HACCP guidelines

UPC	PACK QTY.	U of M
0 77784 05980 7	6	1 ea.



6021 Surface Temperature Thermometer

- ▶ Temperature range: 100°F / 700°F and 50°C / 350°C
- ▶ Monitor grill or any surface temperatures
- ▶ Easy-to-read 2" dial
- ▶ Enclosed design protects coil

UPC	PACK QTY.	U of M
0 77784 06021 6	6	1 ea.



5921N Oven Guide Thermometer

- ▶ Temperature range: 100°F / 600°F
- ▶ Easy-to-read zone guide references
- ▶ Durable stainless steel
- ▶ Hangs or stands

UPC	PACK QTY.	U of M
0 77784 05921 0	6	1 ea.



5984J Instant Read Oven Thermometer

- ▶ Temperature range: 0°F / 220°F
- ▶ 1 1/4" dial with 5" stem
- ▶ Recalibratable

UPC	PACK QTY.	U of M
0 77784 05984 5	1	1 ea.



6246J CharBroiler Thermometer

- ▶ Temperature range: 200°F / 1000°F
- ▶ Hermetically sealed
- ▶ Holder for use on the grill
- ▶ Includes heat deflection sheet for use on CharBroiler

UPC	PACK QTY.	U of M
0 77784 00699 3	4	1 ea.



5932 Oven Dial Thermometer

- ▶ Temperature range: 100°F / 600°F and 50°C / 300°C
- ▶ 3" dial
- ▶ Durable stainless steel
- ▶ Hangs or stands

UPC	PACK QTY.	U of M
0 77784 05932 6	6	1 ea.



5986N Dial Proofing Thermometer

- ▶ Temperature range: 70°F / 130°F and 20°C / 54°C
- ▶ Dial includes proofing zone indicator

UPC	PACK QTY.	U of M
0 77784 05986 9	6	1 ea.



3506FS Oven Dial Thermometer

- ▶ Temperature range: 100°F / 600°F and 50°C / 300°C
- ▶ 2 1/2" dial
- ▶ Durable stainless steel
- ▶ Hangs or stands in oven

UPC	PACK QTY.	U of M
0 77784 03118 6	6	1 ea.

THERMOMETERS


Refrigerator/Freezer Thermometers



5262798 Digital Fridge/Freezer Thermometer ★

- ▶ Large 2" LCD readout with min/max temperature tracking
- ▶ Temperature range: -4°F to 140°F/-20°C to 60°C
- ▶ Attaches with suction cup or adjustable clip
- ▶ Safe zones printed on front panel for easy reference
- ▶ 1 - AAA battery included

UPC	PACK QTY.	U of M
	6	1 ea.



1443 Digital Refrigerator/Freezer Thermometer

- ▶ Temperature range: -4°F / 140°F and -20°C / 60°C
- ▶ Large LCD readout with min/max feature
- ▶ Hangs, stands or attaches with magnet
- ▶ F/C switchable
- ▶ 1 - CR2025 battery included

UPC	PACK QTY.	U of M
	6	1 ea.



1445 Safety Zone Fridge/Freezer Digital Thermometer ★

- ▶ Temperature range: -4°F / 140°F and -20°C / 60°C
- ▶ Track internal temperature of fridge or freezer
- ▶ Programmed with safety zone temperatures
- ▶ Alerts to potential food safety concern

UPC	PACK QTY.	U of M
	6	1 ea.



3503FS Refrigerator/Freezer Thermometer

- ▶ Temperature range: -20°F / 80°F and -30°C / 30°C
- ▶ Safe temperature zone indicators
- ▶ Hangs or attaches with suction cups

UPC	PACK QTY.	U of M
	4	1 ea.



3507FS Refrigerator/Freezer Thermometer

- ▶ Temperature range: -20°F / 80°F and -30°C / 30°C
- ▶ 2½" dial
- ▶ Hangs or stands in the fridge/freezer
- ▶ Safe temperature zone indicators

UPC	PACK QTY.	U of M
	6	1 ea.



3509FS Refrigerator/Freezer Thermometer

- ▶ Temperature range: -20°F / 80°F and -30°C / 30°C
- ▶ Compact size
- ▶ Clips to rack or attaches with suction cup
- ▶ Safe temperature zone indicators
- ▶ Blister carded

UPC	PACK QTY.	U of M
	6	1 ea.

Refrigerator/Freezer Thermometers (cont.)



5924 Refrigerator/Freezer Thermometer

- ▶ Temperature range: -20°F / 80°F and -30°C / 30°C
- ▶ 3" dial
- ▶ Safe temperature zone indicators
- ▶ Hangs or stands

UPC	PACK QTY.	U of M
0 77784 05924 1	6	1 ea.



5925NFS Refrigerator/Freezer Thermometer

- ▶ Temperature range: -20°F / 80°F and -30°C / 30°C
- ▶ Magnified face with shatterproof clear plastic lens
- ▶ Safe temperature zone indicators
- ▶ Hangs or attaches with suction cups

UPC	PACK QTY.	U of M
0 77784 03158 2	6	1 ea.



5926 Economy Hanging Refrigerator/Freezer Thermometer

- ▶ Temperature range: -20°F / 80°F and -30°C / 30°C
- ▶ Bulk pack of 50 per box

UPC	PACK QTY.	U of M
0 77784 05926 5	1	1 ea.



5927 Glycol Refrigerator/Freezer Thermometer

- ▶ Temperature range: -20°F / 60°F and -30°C / 30°C
- ▶ Polypropylene glycol simulates food product temperatures for a more accurate reading
- ▶ Not affected by ambient air changes due to door openings or cold and warm spots
- ▶ Reduces energy costs by mimicking food temperatures
- ▶ Hangs/stands/sits

UPC	PACK QTY.	U of M
0 77784 05927 2	6	1 ea.



5977N Refrigerator/Freezer Thermometer

- ▶ Temperature range: -20°F / 60°F
- ▶ Magnified lens and shatterproof design
- ▶ Safe temperature zone indicators

UPC	PACK QTY.	U of M
0 77784 05977 7	6	1 ea.

THERMOMETERS

Refrigerator/Freezer Thermometers (cont.)




°F/°C
FAHRENHEIT/
CELSIUS



5981N Professional Refrigerator/Freezer Thermometer

- ▶ Temperature range: -30°F / 70°F and -34°C / 20°C
- ▶ Includes HACCP guidelines for safe temperature measurement


UPC	PACK QTY.	U of M
	6	1 ea.



°F/°C
FAHRENHEIT/
CELSIUS

5982N Milk/Beverage Thermometer

- ▶ Temperature range: -40°F / 120°F and -40°C / 50°C
- ▶ Includes adhesive and magnetic backing

UPC	PACK QTY.	U of M
	12	1 ea.




STAINLESS
STEEL

°F/°C
FAHRENHEIT/
CELSIUS

3"
DIAL

5994 Refrigeration Thermometer

- ▶ Temperature range: -30°F / 70°F and -34°C / 20°C
- ▶ Professional quality and accuracy
- ▶ Easy to read 3" dial with safe temperature one guide
- ▶ Durable stainless steel
- ▶ Includes adhesive backing

UPC	PACK QTY.	U of M
	6	1 ea.



Panel Mount Digital Thermometer



 DIGITAL DISPLAY


 BATTERY INCLUDED

 WATER PROOF


°F/°C
FAHRENHEIT/
CELSIUS

9940N Panel Mount Digital Thermometer

- ▶ Temperature range: -40°F / 300°F and -40°C / 150°C
- ▶ Flush and flange mounting options
- ▶ Waterproof housing and probe
- ▶ 10' cable for both air and liquid immersion
- ▶ 1 - AAA battery included

UPC	PACK QTY.	U of M
	4	1 ea.

Precision Thermometers



3503FS Refrigerator/Freezer Thermometer

- ▶ Temperature range: -20°F / 80°F and -30°C / 30°C
- ▶ Safe temperature zone indicators
- ▶ Hangs or attaches with suction cups

UPC	PACK QTY.	U of M
	4	1 ea.



3504 Meat Dial Thermometer

- ▶ Temperature range: 120°F / 210°F
- ▶ 2" dial with USDA guidelines
- ▶ Adjustable temperature indicator
- ▶ Stainless steel 4½" stem

UPC	PACK QTY.	U of M
	6	1 ea.



3505 Candy/Deep Fry Thermometer

- ▶ Temperature range: -40°F / 450°F and -40°C / 230°C
- ▶ 2" dial with candy zones
- ▶ Adjustable pan/kettle clip
- ▶ Temperature indicator
- ▶ 6" stem

UPC	PACK QTY.	U of M
	6	1 ea.



3506FS Oven Dial Thermometer

- ▶ Temperature range: 100°F / 600°F and 50°C / 300°C
- ▶ 2½" dial
- ▶ Durable stainless steel
- ▶ Hangs or stands in oven

UPC	PACK QTY.	U of M
	6	1 ea.



3507FS Refrigerator/Freezer Thermometer

- ▶ Temperature range: -20°F / 80°F and -30°C / 30°C
- ▶ 2½" dial
- ▶ Hangs or stands in the fridge/freezer
- ▶ Safe temperature zone indicators

UPC	PACK QTY.	U of M
	6	1 ea.



3512FS Pocket Test Thermometer

- ▶ Temperature range: 0°F / 220°F
- ▶ 1" magnified lens
- ▶ Protective pocket sleeve

UPC	PACK QTY.	U of M
	6	1 ea.


THERMOMETERS

Precision Thermometers (cont.)



3517 Pocket Test Thermometer

- ▶ Temperature range: 50°F / 550°F
- ▶ 1" magnified lens
- ▶ Protective pocket sleeve

UPC	PACK QTY.	U of M
	6	1 ea.



3518N Digital Cooking Thermometer


- ▶ Temperature range: 32°F / 392°F and 0°C / 200°C
- ▶ Stainless steel probe with 4" silicone cord
- ▶ F/C switch
- ▶ Stand or use with magnet on back for mounting to stove
- ▶ 1 - AAA battery included

UPC	PACK QTY.	U of M
	6	1 ea.



3519FDA Waterproof Digital Instant Read Thermometer with Stepdown Probe


- ▶ Temperature range: -40°F / 450°F and -40°C / 232°C
- ▶ Resolution: 0.1°F/C
- ▶ Easy to grip, pen style design
- ▶ 1.5mm step down probe as recommended by the FDA
- ▶ Waterproof design with instant read and hold feature
- ▶ Auto-shut off feature
- ▶ 1 - LR44 battery included

UPC	PACK QTY.	U of M
	3	1 ea.



3522FS Deep Fry Thermometer

- ▶ Temperature range: 50°F / 550°F and 50°C / 285°C
- ▶ 1 1/4" dial
- ▶ Durable 12" stainless steel stem with adjustable pan clip
- ▶ Temperature indicator

UPC	PACK QTY.	U of M
	6	1 ea.



HACCP Food Safety Thermometers



- ▶ 1" dial with 5" stem
- ▶ Stainless steel construction with shatterproof lens
- ▶ Pocket sleeve with patented built-in calibration feature



1" Dial Instant Read Reduce Cross Contamination Thermometers

6092NFSA

- ▶ Temperature range: 0°F /220°F and -10°C/100°C
- ▶ (5) 1" dial with 5" stem



UPC	PACK QTY.	U of M
0 77784 02023 4	3	1 ea.

6092NBLBC

- ▶ Temperature range: 0°F /220°F and -10°C/100°C
- ▶ Color Coded: Blue - Fish



UPC	PACK QTY.	U of M
0 77784 02558 1	6	1 ea.

6092NBRBC

- ▶ Temperature range: 0°F /220°F and -10°C/100°C
- ▶ Color Coded: Brown - Cooked Meat



UPC	PACK QTY.	U of M
0 77784 02559 8	6	1 ea.

6092NPRBC

- ▶ Temperature range: 0°F /220°F and -10°C/100°C
- ▶ Color Coded: Purple - Allergy



UPC	PACK QTY.	U of M
0 77784 02560 4	6	1 ea.

6092NRDBC

- ▶ Temperature range: 0°F /220°F and -10°C/100°C
- ▶ Color Coded: Red - Raw Meat



UPC	PACK QTY.	U of M
0 77784 02561 1	6	1 ea.

6092NYLBC

- ▶ Temperature range: 0°F /220°F and -10°C/100°C
- ▶ Color Coded: Yellow - Poultry



UPC	PACK QTY.	U of M
0 77784 02562 8	6	1 ea.

HACCP Probe Wipes



9999N

- ▶ 70% isopropyl alcohol
- ▶ 100 single use wipes per box
- ▶ 10 boxes per case
- ▶ Wipe dimensions: 2.5" x 1.25"

UPC	PACK QTY.	U of M
0 77784 09999 5	10	1 ea.



9999T

- ▶ 70% isopropyl alcohol
- ▶ 70 cleansing wipes
- ▶ 10 tubs per case
- ▶ Wipe dimensions: 3.25" x 2.5"

UPC	PACK QTY.	U of M
0 77784 02018 0	10	1 ea.



THERMOMETERS


Special Use Thermometers/Strips



°F/°C
FAHRENHEIT/
CELSIUS

5416J Cup Case Thermometer

- ▶ Temperature range: -40°F /130°F and -40°C/55°C
- ▶ F&C cup case with ring top
- ▶ Brass casing
- ▶ Permacolor filled

UPC	PACK QTY.	U of M
 0 77784 05416 1	4	1 ea.



°F/°C
FAHRENHEIT/
CELSIUS

5948N Tobacco Thermometer

- ▶ Temperature range: 10°F /200°F and -10°C/95°C
- ▶ F&C scales
- ▶ Green color zones for curing process


UPC	PACK QTY.	U of M
 0 77784 05948 7	1	1 ea.



°F/°C
FAHRENHEIT/
CELSIUS

5976N Soil Thermometer

- ▶ Temperature range: 20°F /180°F and 0°C/80°C
- ▶ F&C scales
- ▶ Color coded zone for min, max & optimal soil temperatures

UPC	PACK QTY.	U of M
 0 77784 05976 0	6	1 ea.



RECALIBRATE
NSF

5985N Hot Beverage Thermometer

- ▶ Temperature range: 70°F /190°F
- ▶ 1" dial with 5" stem
- ▶ Pan clip and sleeve included with built-in calibration wrench


UPC	PACK QTY.	U of M
 0 77784 05985 2	4	1 ea.



°F/°C
FAHRENHEIT/
CELSIUS

5997E Cappuccino Frothing Thermometer

- ▶ Temperature range: 120°F /180°F and 50°C/80°C
- ▶ Easy to read zoned dial for optimal frothing temperatures
- ▶ Sealed dial design to prevent fogging

UPC	PACK QTY.	U of M
 0 77784 05997 5	4	1 ea.



RECALIBRATE
°F/°C
FAHRENHEIT/
CELSIUS
NSF

8215N 1 3/4" Dial Hot Beverage Thermometer

- ▶ Temperature range: 0°F /220°F and -10°C/100°C
- ▶ 9" stem with vessel clip
- ▶ Recalibratable
- ▶ Blister carded

UPC	PACK QTY.	U of M
 0 77784 08215 7	6	1 ea.



WATER PROOF
°F/°C
FAHRENHEIT/
CELSIUS

8750 TempRite® Temperature Test Labels

- ▶ Temperature range: 180°F /82°C with accuracy of +/- 2°F (1°C)
- ▶ Adhesive dishwasher safe and waterproof
- ▶ One time use
- ▶ 1 pack of 24 labels

UPC	PACK QTY.	U of M
 0 77784 08750 3	12	1 pk.



WATER PROOF
°F/°C
FAHRENHEIT/
CELSIUS

8751 TempRite® Temperature Test Labels

- ▶ Temperature range: 160°F /71°C with accuracy of +/- 2°F (1°C)
- ▶ Adhesive dishwasher safe and waterproof
- ▶ One time use
- ▶ 1 pack of 24 labels

UPC	PACK QTY.	U of M
 0 77784 08751 0	12	1 pk.



WATER PROOF
°F/°C
FAHRENHEIT/
CELSIUS

8752 TempRite® Temperature Test Labels

- ▶ Temperature range: 170°F /76°C with accuracy of +/- 2°F (1°C)
- ▶ Adhesive dishwasher safe and waterproof
- ▶ One time use
- ▶ 1 pack of 24 labels

UPC	PACK QTY.	U of M
 0 77784 08752 7	12	1 pk.

Special Use Thermometers/Strips (cont.)



8766J TempRite® Temperature Test Strips

- ▶ Temperature range: 160°F /71°C
- ▶ 1 pack of 25 test strips

UPC	PACK QTY.	U of M
	12	1 pk.



8767J TempRite® Temperature Test Strips

- ▶ Temperature range: 180°F /82°C
- ▶ 1 pack of 25 test strips

UPC	PACK QTY.	U of M
	12	1 pk.



8769 TempRite® Temperature 3 in 1 Test Labels

- ▶ Temperature range: 160°F /71°C, 170°F /76°C, 180°F /82°C
- ▶ 3 temperatures for testing
- ▶ 1 pack of 27 labels

UPC	PACK QTY.	U of M
	12	1 pk.



8791 Dishwasher Thermometer ★

- ▶ Temperature range: 32°F/194°F and 0°/90°C
- ▶ Accuracy to ±1.8°F (±1°C)
- ▶ Accurately measures surface temperature of water
- ▶ FDA Food Code compliant for sanitization
- ▶ Designed for use in commercial dishwashers
- ▶ IP67 rated and NIST-Traceable Certificate included

UPC	PACK QTY.	U of M
	6/36	1 ea.



214621J Dishwasher Test Thermometer

- ▶ Temperature range: 0°F /220°F
- ▶ Mercury filled
- ▶ Tube sealed in open face armor case made of high temperature MINLON® plastic
- ▶ Maximum registering
- ▶ Individually packaged

UPC	PACK QTY.	U of M
	1	1 ea.

TAYLOR®

GUIDE FOR TEMPERATURE SAFETY

Temperature Zones

Danger Zone
41°-135°F

Handling Guidelines

- Maintain cold foods at or below 41°F. Maintain hot foods at or above 135°F.
- Potentially hazardous hot food should be cooled rapidly. 135°F cooled to 70°F within 2 hours. 70°F cooled to 41°F within 4 hours. Using shallow pans with a product depth of no greater than 2 inches, the food should be placed in a refrigerator uncovered or loosely covered during the cooling process.
- Never defrost food at room temperature. Use a refrigerator, continuously running cold water, a microwave or cook from frozen state. Frozen food that has been thawed should be cooked or otherwise processed before it may be refrozen.
- Cook foods to the proper internal temperature. Use a metal probe thermometer to ensure food is cooked properly.
- Wash your hands thoroughly with hot soapy water (before and after handling food) for a minimum of 20 seconds.
- Avoid handling food when: ill, have a skin infection, or have cuts on the hands.
- Never cross contaminate from raw to cooked products.
- Wash, rinse and sanitize cutting boards and knives between every use.
- Reheat leftovers to 165°F internal temperature or higher, stirring constantly to cook evenly or microwave to 195°F. Never reheat leftovers more than once.
- Keep kitchens, dining areas and storage rooms free from insects and rodents. Store chemicals away from food.

Taylor® Food Service Thermometers make food safety easy in your cooking environment. For more information on Taylor Precision Products, visit our website: www.taylorusa.com.

THERMOMETERS

PH Meter and Accessories



6580 Digital PH Meter ★

- ▶ PH range: 0.00-14.00
- ▶ Temperature compensation range: 32°F to 122°F / 0°C to 50°C
- ▶ 3 point calibration: 4.01, 6.86, 9.18
- ▶ Calibration powder buffer solution (1 for each calibration point) included
- ▶ Durable hard plastic storage case included
- ▶ (4) LR44 batteries included
- ▶ Replacement probe tip with protective cap (model #6580RP) sold separately

UPC	PACK QTY.	U of M
	5	1 ea.



6580RP PH Meter Replacement Probe ★

- ▶ Replacement probe tip with protective cap for model 6580

UPC	PACK QTY.	U of M
	1	1 ea.

Dial Thermometers/Clocks



166 Patio Clock

- ▶ Brushed silver metal bezel and silk screened graphics
- ▶ Weather resistant and clock movement cover
- ▶ 12" diameter
- ▶ 1 - AA battery required (not included)

UPC	PACK QTY.	U of M
	5	1 ea.



497J Humidiguid Dial Thermometer

- ▶ Temperature range: -60°F/120°F and -50°C/50°C
- ▶ Humidity range: 20% to 90%
- ▶ Brushed silver metal bezel and silk screened graphics
- ▶ Large, easy-to-read face
- ▶ Includes a relative humidity scale
- ▶ 12" diameter

UPC	PACK QTY.	U of M
	5	1 ea.



681T Extra Large Thermometer

- ▶ Temperature range: -60°F/120°F and -50°C/50°C
- ▶ Brushed silver metal bezel and silk screened graphics
- ▶ Large, easy-to-read face
- ▶ Weather resistant construction
- ▶ 18" diameter

UPC	PACK QTY.	U of M
	3	1 ea.



1750 Atomic Clock/Thermometer

- ▶ Temperature range: 14°F/122°F and -10°C/50°C
- ▶ 9.25" atomic wall clock with indoor thermometer
- ▶ Extra large 3.25" LCD readout
- ▶ Atomic time and date with manual setting
- ▶ Calendar with month, date and day
- ▶ 1 - AA battery not included

UPC	PACK QTY.	U of M
	4	1 ea.



1750BK Atomic Clock/Thermometer ★

- ▶ Temperature range: 14°F/122°F and -10°C/50°C
- ▶ 9.25" atomic wall clock with indoor thermometer
- ▶ Extra large 3.25" LCD readout
- ▶ Atomic time and date with manual setting
- ▶ Calendar with month, date and day
- ▶ 1 - AA battery not included

UPC	PACK QTY.	U of M
	4	1 ea.



5265191 Digital Clock/Thermometer ★

- ▶ Temperature range: 14°F/140°F and -10°C/60°C
- ▶ Time displayed in either 12 or 24 hour format
- ▶ Calendar with month, date and day
- ▶ 2 - AA batteries included

UPC	PACK QTY.	U of M
	4	1 ea.

Dial Thermometers/Clocks (cont.)



°F/°C
FAHRENHEIT/
CELSIUS

6714 Indoor/Outdoor 13.25" Dial Thermometer


- ▶ Temperature range: -60°F/120°F and -50°C/50°C
- ▶ ColorTrak design features bright and colorful numbers
- ▶ Framed in a glossy white bezel
- ▶ Weather resistant construction
- ▶ 13.25" diameter

UPC	PACK QTY.	U of M
	4	1 ea.



5630 6" Black and White Bi-Metal Thermometer

- ▶ Temperature range: -60°F/120°F
- ▶ Bold and vibrant silk-screened graphics
- ▶ °F scale only
- ▶ Easy-to-read numerals with clear bezel
- ▶ Wall bracket included for mounting

UPC	PACK QTY.	U of M
	6	1 ea.




°F/°C
FAHRENHEIT/
CELSIUS

 FOOD SAFETY

5636 6" Bi-Metal Thermometer HACCP Cooler/Freezer

- ▶ Temperature range: 0°F/80°F and -17°C/26°C
- ▶ Bold and vibrant silk-screened graphics
- ▶ Easy-to-read numerals with clear bezel
- ▶ Includes color temperature zones for proper food temperature storage
- ▶ Wall bracket included for mounting

UPC	PACK QTY.	U of M
	6	1 ea.




°F/°C
FAHRENHEIT/
CELSIUS

 FOOD SAFETY

5637 6" Bi-Metal Thermometer HACCP Prep/Dry Storage

- ▶ Temperature range: 0°F/100°F and -17°C/37°C
- ▶ Bold and vibrant silk-screened graphics
- ▶ Easy-to-read numerals with clear bezel
- ▶ Includes color temperature zones for proper food temperature storage
- ▶ Wall bracket included for mounting

UPC	PACK QTY.	U of M
	6	1 ea.




°F/°C
FAHRENHEIT/
CELSIUS

 FOOD SAFETY

5680 13.25" Thermometer HACCP Cooler/Freezer

- ▶ Temperature range: 0°F/80°F and -17°C/26°C
- ▶ Bold and vibrant silk-screened graphics
- ▶ Easy-to-read numerals with white bezel
- ▶ Includes color temperature zones for proper food temperature storage

UPC	PACK QTY.	U of M
	4	1 ea.




°F/°C
FAHRENHEIT/
CELSIUS

 FOOD SAFETY

5681 13.25" Thermometer HACCP Prep/Dry Storage

- ▶ Temperature range: 0°F/100°F and -17°C/37°C
- ▶ Bold and vibrant silk-screened graphics
- ▶ Easy-to-read numerals with white bezel
- ▶ Includes color temperature zones for proper food temperature storage

UPC	PACK QTY.	U of M
	4	1 ea.

THERMOMETERS

Window/Wall Thermometers



°F/°C
FAHRENHEIT/
CELSIUS

1105J 12"x2" Dry Storage Thermometer

- ▶ Temperature range: 0°F/120°F and -30°C/50°C
- ▶ Easy-to-read in poor lighting
- ▶ Packed in individual carton
- ▶ Permacolor® filled solution with red color

UPC	PACK QTY.	U of M
	12	1 ea.



°F/°C
FAHRENHEIT/
CELSIUS

5132N 8 1/8"x2 1/2" Utility Wall Thermometer

- ▶ Temperature range: -40°F/120°F and -40°C/50°C
- ▶ White aluminum back with plastic end caps for secure mounting
- ▶ Large, easy-to-read face
- ▶ Weather resistant and rustproof
- ▶ Permacolor® filled solution with red color

UPC	PACK QTY.	U of M
	6	1 ea.



°F/°C
FAHRENHEIT/
CELSIUS

5154 7 5/8"x2 3/8" Wall Thermometer

- ▶ Temperature range: -40°F/120°F and -40°C/50°C
- ▶ Curved look with large, easy-to-read numerals in bright red & blue
- ▶ Includes aluminum bracket for mounting
- ▶ Weather resistant and rustproof
- ▶ Permacolor® filled solution with red color

UPC	PACK QTY.	U of M
	6	1 ea.



°F/°C
FAHRENHEIT/
CELSIUS

1106J 12"x2" Cold/Dry Storage Thermometer

- ▶ Temperature range: -50°F/70°F and -40°C/20°C
- ▶ Easy-to-read in poor lighting
- ▶ Packed in individual carton
- ▶ Permacolor® filled solution with red color

UPC	PACK QTY.	U of M
	12	1 ea.



°F/°C
FAHRENHEIT/
CELSIUS

5135N 8 7/8"x2 1/4" Wall Thermometer

- ▶ Temperature range: -60°F/120°F and -50°C/50°C
- ▶ White aluminum for indoor or outdoor use
- ▶ Large, easy-to-read face
- ▶ Weather resistant and rustproof
- ▶ Permacolor® filled solution with red color

UPC	PACK QTY.	U of M
	6	1 ea.



°F/°C
FAHRENHEIT/
CELSIUS

5316N 8"x2 1/2" Window Thermometer

- ▶ Temperature range: -40°F/120°F and -40°C/50°C
- ▶ White aluminum back with large, easy-to-read numerals
- ▶ Rustproof bracket with adjustable design for multi-directional viewing
- ▶ Permacolor® filled solution with red color

UPC	PACK QTY.	U of M
	6	1 ea.



°F/°C
FAHRENHEIT/
CELSIUS

5109 1 1/2"x3 1/4" Jumbo Wall Thermometer

- ▶ Temperature range: -40°F/120°F and -40°C/50°C
- ▶ Bright red reading tube with extra large colorful numbers
- ▶ Weather resistant and rustproof for quick, accurate temperature checks inside or outside
- ▶ Permacolor® filled solution with red color

UPC	PACK QTY.	U of M
	6	1 ea.



°F/°C
FAHRENHEIT/
CELSIUS

5153 7 5/8"x2 3/8" Window Thermometer

- ▶ Temperature range: -40°F/120°F and -40°C/50°C
- ▶ Curved look with large, easy-to-read numerals in bright blue & green
- ▶ Includes aluminum bracket for mounting
- ▶ Weather resistant and rustproof
- ▶ Permacolor® filled solution with red color

UPC	PACK QTY.	U of M
	6	1 ea.



5321N 3 1/2" Dial Stick-on Window Thermometer

- ▶ Temperature range: -40°F/120°F
- ▶ Read outside temperature from inside
- ▶ Easy to apply suction cup mount
- ▶ Weather resistant and rustproof

UPC	PACK QTY.	U of M
	6	1 ea.

Window/Wall Thermometers (cont.)



°F/°C
FAHRENHEIT/
CELSIUS

5327 9³/₄"x1¹/₄" Indoor/Outdoor Thermometer

- ▶ Temperature range: -40°F/100°F and -40°C/40°C
- ▶ Read indoor and outdoor temperatures from inside
- ▶ Bold numerals in bright blue and red
- ▶ Permacolor® filled solution with red (indoor) and blue (outdoor) colors


UPC	PACK QTY.	U of M
	6	1 ea.



MULTIUSE
°F/°C
FAHRENHEIT/
CELSIUS

5329 9³/₄"x1⁷/₈" Indoor/Outdoor Thermometer

- ▶ Temperature range: -40°F/120°F and -40°C/40°C
- ▶ Humidity range: 10% to 80%
- ▶ Dial to read indoor humidity
- ▶ Large, easy-to-read face
- ▶ Permacolor® filled solution with red (indoor) and blue (outdoor) colors


UPC	PACK QTY.	U of M
	4	1 ea.



°F/°C
FAHRENHEIT/
CELSIUS

5380N 1 3/4" Dial Stick-on Window Thermometer

- ▶ Temperature range: -40°F/120°F and -40°C/50°C
- ▶ Indoor/outdoor multi-purpose thermometer easily mounts with double-faced adhesive
- ▶ Weather resistant and rustproof


UPC	PACK QTY.	U of M
	12	1 ea.



MULTIUSE

5504 Indoor Humidiguid and Thermometer

- ▶ Temperature range: 20°F/100°F
- ▶ Humidity range: 10% to 80%
- ▶ Displays relative humidity and temperature
- ▶ 4" square case hangs or stands

UPC	PACK QTY.	U of M
	6	1 ea.




MULTIUSE
°F/°C
FAHRENHEIT/
CELSIUS

BATTERY
NOT INCLUDED

5566 Digital Hygrometer with Thermometer

- ▶ Temperature range: -40°F/158°F and -40°C/70°C
- ▶ Humidity range: 10%-95%
- ▶ Large, easy-to-read LCD
- ▶ Wall mount or table top
- ▶ 300 days of continuous reading battery life
- ▶ 2 - AAA batteries not included

UPC	PACK QTY.	U of M
	12	1 ea.




INDOOR
TEMPERATURE

INDOOR
HUMIDITY

BATTERIES
INCLUDED

1745BK Indoor Thermometer with Hygrometer

- ▶ Indoor Temperature Range: 14°F/122°F and -10°C/50°C
- ▶ Humidity Range: 20-90%
- ▶ Read and record indoor temperature and humidity
- ▶ Clock function
- ▶ 2 - LR44 batteries included

UPC	PACK QTY.	U of M
	6	1 ea.

THERMOMETERS

Max/Min Thermometers




 AAA
 BATTERY INCLUDED

°F/°C
 FAHRENHEIT/
 CELSIUS

1441E Digital Max/Min Thermometer

- ▶ Temperature range: -20°F/120°F and -29°C/50°C
- ▶ Records temperature readings for 7 days at a time
- ▶ Dual 3 meter probes for independent readings
- ▶ 2 - AAA batteries included

UPC	PACK QTY.	U of M
	4	1 ea.



5458 Max/Min Thermometer

- ▶ Temperature range: -40°F/120°F
- ▶ Magnet reset, registers high and low reading from last setting
- ▶ Mercury filled

UPC	PACK QTY.	U of M
	1	1 ea.




 AAA
 BATTERY INCLUDED

°F/°C
 FAHRENHEIT/
 CELSIUS

1442 Critical Care Thermometer


- ▶ Temperature range: -40°F/221°F and -40°C/105°C
- ▶ For monitoring temperature critical materials
- ▶ Programmable high and low limit alarms
- ▶ 96 hour memory of high and low temperatures
- ▶ Records a history of alarm breaches included time and duration
- ▶ Dual 6' glycol-tolerant probes
- ▶ Password protected
- ▶ 2 - AAA batteries included

UPC	PACK QTY.	U of M
	1	1 ea.



5459 Max/Min Thermometer

- ▶ Temperature range: -40°C/50°C
- ▶ Magnet reset, registers high and low reading from last setting
- ▶ Mercury filled


UPC	PACK QTY.	U of M
	1	1 ea.



°F/°C
 FAHRENHEIT/
 CELSIUS

5460 Max/Min Thermometer

- ▶ Temperature range: -40°F/120°F and -40°C/50°C
- ▶ Push button reset and magnet reset
- ▶ Permacolor™ filled

UPC	PACK QTY.	U of M
	4	1 ea.

Pocket Case Thermometers



- ▶ Plastic case included
- ▶ Permacolor™ filled

214121J

- ▶ Temperature range: -50°F/120°F

UPC	PACK QTY.	U of M
0 77784 01354 0	12	1 ea.

214201J

- ▶ Temperature range: 0°F/220°F

UPC	PACK QTY.	U of M
0 77784 01086 0	12	1 ea.

214241J

- ▶ Temperature range: -15°C/105°C

UPC	PACK QTY.	U of M
0 77784 01355 7	12	1 ea.

214321J

- ▶ Temperature range: -40°C/50°C

UPC	PACK QTY.	U of M
0 77784 01356 4	12	1 ea.



THERMOMETERS

Digital Pocket Test Thermometers - Comparison Guide



GOOD



3516FS



9840RB



1476FDA



9840PRN



9841RB



3519FDA

Product Specifications	3516FS	9840RB	9840PRN	9841RB	1476FDA
Temperature range:	-40°/302°F	-40°/302°F -40°/150°C	-40°/302°F -40°/150°C	-40°/500°F -40°/260°C	-40°/450°F -40°/232°C
Accuracy:	+/- 2°F	+/- 2°F	+/- 2°F	+/- 2°F	+/- 2°F
Certifications:	NSF	NSF	NSF	NSF	NSF
Dimensions: • Stem Length • Probe Diameter	4.75" 3.8mm	4.69" 1.5mm	4.69" 1.5mm	4.69" 1.5mm	3.43" 1.6mm
Features: • Waterproof • °F & °C Selectable • On/Off • Hold • Auto Shut Off • Protective Rubber Boot • 1.5mm Step Down Probe • Calibration • Max/Min Memory	✓	✓	✓	✓	✓
LCD Size:	0.3"	0.4"	0.4"	0.4"	0.6"
Battery Type:	LR44 (included)	LR44 (included)	LR44 (included)	LR44 (included)	LR44 (included)
Warranty:	1 Year	1 Year	1 Year	1 Year	1 Year

BETTER

BEST



3519FDA	3519PRFDA	9842FDA	9848EFDA	9877FDA	9878E	9878EPR
-40°/450°F -40°/232°C	-40°/450°F -40°/232°C	-40°/450°F -40°/232°C	-40°/450°F -40°/232°C	-40°/450°F -40°/232°C	-40°/500°F -40°/260°C	-40°/500°F -40°/260°C
+/- 2°F	+/- 2°F	+/- 2°F	+/- 2°F	+/- 2°F	+/- 1°F	+/- 1°F
NSF	NSF	NSF	NSF	NSF	NSF	NSF
3.19" 1.5mm	3.19" 1.5mm	4.81" 1.5mm	3.00" 1.5mm	2.81" 1.5mm	5.11" 1.5mm	5.11" 1.5mm
✓	✓	✓	✓	✓	✓	✓
✓	✓	✓	✓	✓	✓	✓
✓	✓	✓	✓	✓	✓	✓
✓	✓	✓	✓	✓	✓	✓
✓	✓	✓	✓	✓	✓	✓
✓	✓	✓	✓	✓	✓	✓
			✓ (max)	✓	✓	✓
0.5"	0.5"	0.5"	0.5"	0.3"	0.4"	0.4"
LR44 (included)	LR44 (included)	LR44 (included)	CR2032 (included)	CR1225 (included)	CR2032 (included)	CR2032 (included)
1 Year	1 Year	1 Year	1 Year	1 Year	1 Year	1 Year